

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



**SAMSUNG**

Nazwa **Monitor Samsung SMART Signage PM32F (LH32PMFPBGC/EN)**

Cena **2 690,00 zł**

Producent **Samsung**

## OPIS PRODUKTU

### Podstawowe cechy:

Przekątna: 32"/81.3cm • Rozdzielczość: 1920x1080, 16:9 • Jasność: 400cd/m<sup>2</sup> • Kontrast: 5.000:1 (statyczny), brak danych (dynamiczny) • Czas reakcji: 8ms • Kąt widzenia: 178°/178° • Częstotliwość odświeżania: 60Hz • Złącza: DVI, 2x HDMI, 2x DisplayPort 1.2 • Dodatkowe złącza: 2x USB, LAN, WLAN • VESA: 200x200 (wolne) • Pobór mocy: 61W (praca), 0.5W (czuwanie) • Wymiary (SxWxG): 72.1x42x3cm • Waga: 5.60kg • Cechy szczególne: podświetlenie LED, głośniki (2x 10W), Tizen OS • Gwarancja: trzy lata Panel

Diagonal Size 32"

Type 60Hz E-LED BLU

Resolution 1920\*1080 (Full HD)

Pixel Pitch (mm) 0.360(H) x 0.360(V)

Active Display Area (mm) 698.4(H) x 392.85(V)

Brightness (Typ.) 400 nit

Contrast Ratio 5000:1

Viewing Angle (H/V) 178:178

Response Time (G-to-G) 8ms

Display Colors 10bit Dithering - 1.07 Billion

Color Gamut 72%

Haze 2%

Display

Dynamic C/R Mega

H-Scanning Frequency 30 ~ 81 kHz

V-Scanning Frequency 48 ~ 75 Hz

Maximum Pixel Frequency 148.5 MHz

Sound

Speaker Type Built in Speaker (10W + 10W)

Connectivity

Input

RGB DVI-I (D-Sub Common), Display Port 1.2 (2)

Video HDMI (2)

AudioStereo mini Jack

UsbUSB 2.0 x 2

Output

RGBDP1.2(Loop-out)

VideoN/A

AudioStereo mini Jack

Power OutN/A

External ControlRS232C(in/out) thru Stereo Jack, RJ45

External SensorN/A

TunerYes(only for NA)

Power

TypeInternal

Power SupplyAC 100 - 240 V~ (+/- 10 %), 50/60 Hz

Power Consumption

Max[W/h]88.0

Typical[W/h]EU 61, US 42, WW 61

BTU(Max)300.08

Sleep modeless than 0.5W

Off modeless than 0.5W

Mechanical Specification

Dimension (mm)

Set721.2 x 415.6 x 29.9

Package796 X 484 X 132

Weight (kg)

Set5.6

Package7

VESA Mount (mm)200x200

Protection GlassN/A

Stand TypeFoot Stand (Optional)

Media Player Option TypeN/A

Bezel Width (mm)8.9(Even)

Operation

Recommended Usage Hours16/7

Operating Temperature 0.0 ~ 40.0

Humidity 10.0 % ~ 80.0 %

Feature

Key FeaturesSlim & Light Signage with Built-in MagicInfo S4, SSSP 4.0

Special Features H/W : Temperature Sensor, Video Wall(15x15(OSD)), Video Wall Daisy Chain(16), Pivot Display, Clock Battery(80hrs Clock Keeping), Built in Speaker(10W x 2), WiFi Module Embedded, Tuner(only for NA), IP5x, Center IR

S/W : Clone(to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC,Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital Daisy Chain(HDCP Support), Firmware Update by Network, New Home Screen, PC-less VideoWall, Multi Channel, Mobile Control, Event Schedule, Backup Player Internal Player

ProcessorCortex-A12 1.3GHz Quad Core CPU

On-Chip Cache MemoryL1 (I/D) : 32KB / 32KB L2 (Unified) : 1MB

Clock Speed1.3GHz CPU Quad

Main Memory Interface2.5GB 3 channel 96bit DDR3-933 (1866MHz)

Graphics2D & 3D Graphics Engine - Up to 3840x2160p. 32bpp - Supports OpenGL ES

Storage (FDM)8GB (3.75GB Occupied by O/S, 4.25GB Available, )

MultimediaVideo Decoder - MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC - VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9 Audio DSP (Decoder) - AC3 (DD), MPEG, DTS and etc.

IO PortsUSB 2.0

Operating SystemTizen 2.4 (VDLinux)

Certification

SafetyCB (Europe) : IEC60950-1/EN60950-1 CCC (China) : GB4943.1-2011 PSB (Singapore ) :  
PSB+IEC60950-1 NOM (Mexico ) : NOM-001-SCFI-1993 IRAM (Argentina ) : IRAM+IEC60950-1 SASO (Saudi  
Arabia ) : SASO+IEC60950-1 BIS(India) : IEC60950-1 / IS13252 NOM(Mexico) : Tuner : NOM-001-SCFI-1993  
Tunerless : NOM-019-SCFI-1998 KC(Korea) : K 60950-1 EAC(Russia) : EAC+IEC60950-1  
INMETRO(Brazil) : INMETRO+IEC60950-1 BSMI(Taiwan) : BSMI+IEC60950-1 RCM(Australia) :  
IEC60950-1/AS/NZS 60950-1 UL(USA) : cUL60950-1 CSA (Canada) : cUL TUV (Germany) : CE NEMKO  
(Norway) : CE  
EMCFCC (USA) Part 15, Subpart B Class A CE (Europe) : EN55022:2006+A1:2007  
EN55024:1998+A1:2001+A2:2003 VCCI (Japan) : VCCI V-3 /2010.04 Class A KCC/EK (Korea) : Tuner : KN13  
/ KN20 Tunerless : KN22 / KN24 BSMI (Taiwan) : CNS13438 (ITE EMI) Class A / CNS13439  
(AV EMI) / CNS14409 (AV EMS) / CNS14972 (Digital) C-Tick (Australia) : AS/NZS CISPR22:2009 CCC(China)  
:GB9254-2008 GB17625.1-2012 GOST(Russia/CIS) : GOST R 51317 Series,  
GOST 22505-97 EN55022:2006+A1:2007  
EN55024:1998+A1:2001+A2:2003  
EnvironmentN/A  
Accessory  
IncludedQuick Setup Guide, Regulatory Guide , Warranty Card, Power Cord, Remote Controller,  
Batteries, RS232C(IN) adapter, Cover Jack  
Optional  
StandSTN-L3240E  
Mount □□□□□□□□ □□□□□□□□WMN4070SD  
SpecialtyCML400XJ  
Media Player  
Media Player  
Media PlayerSBB(Not attachble)