

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



**SAMSUNG**

Nazwa

**Monitor Samsung SMART Signage QM32R  
(LH32QMREBGCXEN)**

Cena

**3 242,00 zł**

Producent

**Samsung**

## OPIS PRODUKTU

Panel

Diagonal Size

32"

Type

Edge LED BLU

Resolution

1920\*1080 (Full HD)

Pixel Pitch(mm)

0.360 x 0.360

Active Display Area(mm)

698.4(H) x 392.85(V)

Brightness(Typ.)

400 nit

Contrast Ratio

5000:1

Viewing Angle(H/V)

178/178

Response Time(G-to-G)

8ms(Typ.)

Display Colors

16.7M(True Display) 1.07B(Ditherd 10bit)

Color Gamut

72%

Operation Hour

24/7

Haze

2%

Display

Dynamic C/R

MEGA

H-Scanning Frequency

30 ~ 81kHz

V-Scanning Frequency

48 ~ 75Hz

Maximum Pixel Frequency

594MHz

Sound

Speaker Type

Built in Speaker(10W + 10W)

Connectivity

Input

RGB

Display Port 1.2 (1)

Video

HDMI 2.0 (1)

HDCP

HDCP2.2

Audio

Stereo mini Jack, HDMI

USB

USB 2.0 x 2

Output

RGB

HDMI 2.0 (Loop-out)

Audio

Stereo mini Jack

External Control

RS232C(in/out) thru stereo jack, RJ45

External Sensor

IR

Power

Type

Internal

Power Supply

AC 100 - 240 V~ (+/- 10 %), 50/60 Hz

Power Consumption

Max[W/h]

72

Typical[W/h]

44

Rating[W/h]

65

BTU(Max)

245.5

Sleep mode

0.5

Mechanical Specification

Dimension (mm)

Set

725.1 x 419.6 x 34.6

Package

812 x 513 x 120

Weight (kg)

Set

5.7

Package

8.0

VESA Mount (mm)

200 X 200

Stand Type

Foot Stand (Optional)

Bezel Width (mm)

8.8mm(U/L/R/B)

Operation

Operating Temperature

0 ° ~ 40 °

Humidity

10 % ~ 80 %

Feature

Key Features

FHD Signage Display Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0

Orientation

N/A

Remote Control

N/A

Special Features

H/W:Temperature Sensor,Pivot Display, Clock Battery(168hrs Clock Keeping), Built in Speaker(10W 2ch), Video Wall Daisy Chain(HDCP2.2:4EA,HDCP1.4:7EA), IP5x Rating, Wi-Fi/BT S/W:Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)

Internal Player

Processor

Cortex A72 1.7GHz Quad-Core CPU

On-Chip Cache Memory

L1 Instruction Cache : 48KB L1 Data Cache : 32KB L2 Cache : 2MB

Clock Speed

1.7GHz

Main Memory Interface

2.5GB LPDDR4 1.5GHz 64bit

Graphics

Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.)

Storage (FDM)

8GB (3.88GB Occupied by O/S, 4.12GB Available)

Multimedia

\*Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9 \*Audio Decoder : AC3 (DD), MPEG

IO Ports

USB 2.0

Operating System

Tizen 4.0 (VDLinux)

Certification

Safety

60950-1

EMC

Class B

Security

802.1x (WPA2 Enterprise) : EAP-TLS, EAP-TTLS, EAP-PEAP

Accessory

Included

Quick Setup Guide, Warranty Card, Power Cord, Remote Controller, Batteries