

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



SAMSUNG

Nazwa

**Monitor Samsung SMART Signage QM50R
(LH50QMREBGXEN)**

Cena

0,00 zł

Producent

Samsung

OPIS PRODUKTU

Panel

Diagonal Size

50"

Type

Edge LED BLU

Resolution

3840*2160 (4K UHD)

Pixel Pitch(mm)

0.285 x 0.285

Active Display Area(mm)

1095.84(H) x 616.41(V)

Brightness(Typ.)

500 nit

Contrast Ratio

4000:1

Viewing Angle(H/V)

178/178

Response Time(G-to-G)

8ms(Typ.)

Display Colors

16.7M(True Display) 1.07B(Ditherd 10bit)

Color Gamut

92% (DCI-P3, CIE 1976)

Operation Hour

24/7

Haze

25%

Display

Dynamic C/R

MEGA

H-Scanning Frequency

30 ~ 81kHz

V-Scanning Frequency

48 ~ 75Hz

Maximum Pixel Frequency

594MHz

Sound

Speaker Type

Built in Speaker(10W + 10W)

Connectivity

Input

RGB

DVI-D, Display Port 1.2 (1)

Video

HDMI 2.0 (2)

HDCP

HDCP2.2

Audio

Stereo mini Jack, DVI, HDMI/Audio(Common)

USB

USB 2.0 x 2

Output

RGB

HDMI 2.0 (Loop-out)

Audio

Stereo mini Jack

External Control

RS232C(in/out) thru stereo jack, RJ45

External Sensor

IR

Power

Type

Internal

Power Supply

AC 100 - 240 V~ (+/- 10 %), 50/60 Hz

Power Consumption

Max[W/h]

TBD

Typical[W/h]

TBD

Rating[W/h]

TBD

BTU(Max)

TBD

Sleep mode

0.5

Mechanical Specification

Dimension (mm)

Set

1121.4 x 643.9 x 46.3

Package

TBD

Weight (kg)

Set

TBD
Package
TBD
VESA Mount (mm)
200 X 200
Stand Type
Foot Stand (Optional)
Bezel Width (mm)
9.2mm(U/L/R), 11.2mm(B)
Operation
Operating Temperature
0 ° ~ 40 °
Humidity
10 % ~ 80 %
Feature
Key Features
UHD Signage Display Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0
Orientation
N/A
Remote Control
N/A
Special Features
H/W: Temperature Sensor,Pivot Display, Clock Battery(168hrs Clock Keeping), Built in Speaker(10W 2ch), Video Wall Daisy Chain(HDCP2.2:4EA,HDCP1.4:7EA), IP5x Rating, Wi-Fi/BT S/W: Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)
Internal Player
Processor
Cortex A72 1.7GHz Quad-Core CPU
On-Chip Cache Memory
L1 Instruction Cache : 48KB L1 Data Cache : 32KB L2 Cache : 2MB
Clock Speed
1.7GHz
Main Memory Interface
2.5GB LPDDR4 1.5GHz 64bit
Graphics
Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.)
Storage (FDM)
8GB (3.88GB Occupied by O/S, 4.12GB Available)
Multimedia
*Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9 *Audio Decoder : AC3 (DD), MPEG
IO Ports
USB 2.0
Operating System
Tizen 4.0 (VDLinux)
Certification
Safety
60950-1
EMC
TBD
Security
TBD
Accessory
Included

Quick Setup Guide, Warranty Card, Power Cord, Remote Controller, Batteries