

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



SAMSUNG

Nazwa **Monitor Samsung SMART Signage QM55R-B**

Cena **0,00 zł**

Producent **Samsung**

OPIS PRODUKTU

Panel

Diagonal Size

55"

Type

Edge LED BLU

Resolution

3840*2160 (4K UHD)

Pixel Pitch(mm)

0.315 x 0.315

Active Display Area(mm)

1209.6(H) x 680.4(V)

Brightness(Typ.)

500 nit

Contrast Ratio

4000:1

Viewing Angle(H/V)

178/178

Response Time(G-to-G)

8ms(Typ.)

Display Colors

16.7M(True Display)1.07B(Ditherd 10bit)

Color Gamut

92% (DCI-P3, CIE 1976)

Operation Hour

24/7

Haze

25%

Display

Dynamic C/R

MEGA

H-Scanning Frequency

30 ~ 81kHz

V-Scanning Frequency

48 ~ 75Hz

Maximum Pixel Frequency

594MHz

Sound

Speaker Type

Built in Speaker(10W + 10W)

Connectivity

Input

RGB

Display Port 1.2 (1)

Video

HDMI 2.0 (2)

HDCP

HDCP2.2

Audio

Stereo Mini Jack, HDMI/Audio(Common)

USB

USB 2.0 x 2

Output

Audio

Stereo mini Jack

External Control

RS232C(in/out) thru stereo jack, RJ45

External Sensor

IR

Power

Type

Internal

Power Supply

AC 100 - 240 V, 50/60 Hz

Power Consumption

Max[W/h]

143.0

Typical[W/h]

108.0

Rating[W/h]

130.0

BTU(Max)

487.6

Sleep mode

0.5

Mechanical Specification

Dimension (mm)

Set

1235.1 x 707.9 x 46.3

Package

1402 x 858 x 163

Weight (kg)

Set

18.1

Package

23.6

VESA Mount (mm)

200 X 200

Stand Type

Foot Stand (Optional)

Bezel Width (mm)

9.2mm(U/L/R), 11.2mm(B)

Operation

Operating Temperature

0 ° ~ 40 °

Humidity

10.0 % ~ 80.0 %

Feature

Key Features

UHD Signage Display Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0

Orientation

Landscape / Portrait

Remote Control

N/A

Special Features

H/W : Temperature Sensor, Pivot Display, Clock Battery(168hrs Clock Keeping), Built in Speaker(10W 2ch), IP5x Rating, Wi-Fi S/W : Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)

Internal Player

Processor

Cortex A72 1.7GHz Quad-Core CPU

On-Chip Cache Memory

L1 Instruction Cache : 48KB L1 Data Cache : 32KB L2 Cache : 2MB

Clock Speed

1.7GHz

Main Memory Interface

2.5GB LPDDR4 1.5GHz 64bit

Graphics

Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.)

Storage (FDM)

8GB (3.88GB Occupied by O/S, 4.12GB Available)

Multimedia

*Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9 *Audio Decoder : AC3 (DD), MPEG

IO Ports

USB 2.0

Operating System

Tizen 4.0 (VDLinux)

Certification

Safety

60950-1

EMC

Class B

Security

802.1x(WPA2 Enterprise) : EAP-TLS, EAP-TTLS, EAP-PEAP

Accessory

Included

Quick Setup Guide, Warranty Card, Power Cord, Remote Controller, Batteries

Optional
Stand
STN-L4355F
Mount
WMN4070SE (Land Only) WMN750ME
Specialty
CML400XK
Media Player
Media Player
Media Player
N/A