

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



SAMSUNG

Nazwa **Monitor Samsung SMART Signage SL46B**

Cena **0,00 zł**

Producent **Samsung**

OPIS PRODUKTU

TECH SPECS

Display

H-Scanning Frequency

30 - 81 KHz

Maximum Pixel Frequency

148.5 MHz

V-Scanning Frequency

48 - 75 Hz

Panel

Diagonal Size

46"

Type

S-PVA

Resolution

1,920 x 1,080

Pixel Pitch(mm)

0.53025 (H) x 0.53025 (V) mm

Active Display Area

1,018.08 (H) X 572.67 (V) mm

Brightness (Typical)

1,500 cd/□

Contrast Ratio (Dynamic)

10,000:1

Viewing Angle (H/V)

178 / 178 ° (CR > 10)

Response Time (G-to-G)

8 ms

Display Colour

16.7 M

Colour Gamut

72 %
Contrast Ratio
4,000:1
Connectivity
Input
RGB
D-SUB, DVI-D
Video
USB, HDMI, CVBS, Component (by D-SUB)
Audio
RCA(L/R) , Stereo Mini Jack
Output
RGB
DVI-D (Loop-out)
Video
N/A
Audio
Stereo Mini Jack
Power Out
N/A
External Control
RJ45, RS232C (In/Out)
External Sensor
Attached
Mechanical Specification
Dimension
Set Dimension (WxHxD)
1,049.4 x 602.6 x 125 mm
Package Dimension (WxHxD)
1,145 x 726 x 300 mm
Weight
Set Weight
26.8 kg
Package Weight
32.6 kg
VESA Mount
600 x 400mm
Protection Glass
N/A
Stand Type
N/A
Media Player Option Type
Embedded, SIM (Slide in Module)
Operation
Operating Temperature
0° - 30°(Direct Sunlight)
Humidity
10 - 80 %
General Features
Key
Extremely High Brightness
Special
Plug and Play, MagicInfo Lite, Slide in Module, Digital Daisy Chains, Built in Speakers, Lamp Error
Detection, Anti Image Retention, Temperature Sensor, RS232C/RJ45 MDC, PIP/PBP, Video Wall(10x10),
Pivot Display, Button Lock, Smart Scheduling

Power

Energy Efficiency Class

N/A

Power Supply

AC 100 - 240 V~ (+/- 10 %), 50/60 Hz

Power Consumption

Off Mode

Less than 1 W

On Mode

440 W (Max) / 356 W (Typ)

Sleep Mode

Less than 1 W

Type

Internal

Embedded PC

CPU

N/A

N/B

N/A

S/B

N/A

GPU

N/A

FDM/HDD

N/A

Memory

N/A

Ethernet

N/A

Connectivity

USB

N/A

Output

N/A

Others

N/A

Certification

EMC

FCC (USA) FCC Part 15, Subpart B class A CE (Europe) EN55022, EN55024 VCCI (Japan) V-3 (CISPR22) KCC

(Korea) :KN22, KN24 BSMI (Taiwan) : CNS13438 (CISPR22) C-Tick (Australia) : AS/NZS3548 (CISPR22)

CCC(China) :GB 9254-2008, GB 17625.1-2003

Environment

N/A

Safety

UL (USA) : UL 60950-1 CSA (Canada) : CSA C22.2 No. 60950-1 TUV (Germany) : EN60950-1 NEMKO

(Norway) : EN60950-1 KC (Korea) : K60950-1 CCC (China) : GB 4943-2001 PSB (Singapore) : IEC60950-1

GOST (Russia) : IEC60950-1, EN55022 SIQ (Slovenia) : IEC60950-1, EN55022 PCBC (Poland) : IEC60590-1,

EN55022 NOM (Mexico) : NOM-019-SCFI-1993 IRAM (Argentina) : IEC60950-1 SASO (Saudi Arabia) :

IEC60950-1

Accessory

Included

Quick Setup Guide, Warranty Card, Application CD, Power Cord, Remote Controller, Batteries, D-Sub

Cable

Optional

Mount

N/A
Specialty
N/A
Stand
N/A