

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



**SAMSUNG**

Nazwa **Monitor zewnętrzny Samsung Outdoor Series 460DR-2**

Cena **0,00 zł**

Producent **Samsung**

## OPIS PRODUKTU

### TECH SPECS

Panel

Diagonal Size

46"

Type

S-PVA (E-DID)

Resolution

1,920 x 1,080

Pixel Pitch (mm)

0.53025 (H) x 0.53025 (V) mm

Active Display Area

1018.08 (H) X 572.67 (V) mm

Brightness

1500 cd/□

Contrast Ratio (Dynamic)

10,000:1 (TBD)

Viewing Angle (Horizontal/Vertical)

178 / 178 °

Response Time (G-to-G)

8 ms

Display Colour

16.7 M

Color Gamut

50 %

Contrast Ratio

4,000:1

Display

H-Scanning Frequency

30 - 81 KHz

Maximum Pixel Frequency

148.5 MHz

V-Scanning Frequency

56 - 85 Hz

Connectivity

Input

RGB

Analog D-SUB, DVI-D, Display Port

Video

CVBS, HDMI1, HDMI2, Component (D-SUB 15 Pin)

Audio

Stereo Mini Jack

Output

RGB

N/A

Video

N/A

Audio

Stereo Mini Jack

Power Out

N/A

External Control

RJ45, RS232C (In / Out)

External Sensor

N/A

Mechanical Specification

Dimension

Set Dimension (WxHxD)

1,047.4 x 632.8 x 151.5 mm

Package Dimension (WxHxD)

1,162.0 x 755.0 x 325.0 mm

Weight

Set Weight

24 kg

Package Weight

30 kg

VESA Mount

400 x 400 mm

Protection Glass

N/A

Stand Type

N/A

Media Player Option Type

N/A

Operation

Operating Temperature

0 - 40 °C

Humidity

10 - 80 %

General Feature

Key

Extremely High Brightness

Special

Kit Type, Air Conditioning Guide, Lamp Error Detection, Anti Retention, Temperature Sensor, RS232C / RJ45 MDC, Plug and Play (DDC2B), PIP / PBP, Video Wall (10 x 10), Pivot Display, Button Lock, Smart

Scheduling, Smart F/W Update

Power

Energy Rating (Stars)

N/A

Power Supply

AC 100 - 240 V ~ (+ / - 10 %), 50 / 60 Hz

Power Consumption

Off Mode

Less than 1 W

On Mode

420 W (Max, TBD) / 354 W (Typ, TBD)

Sleep Mode

Less than 1 W

Type

Internal

Embedded PC

CPU

N/A

N/B

N/A

S/B

N/A

GPU

N/A

FDM/HDD

N/A

Memory

N/A

Ethernet

N/A

Connectivity

USB

N/A

Output

N/A

Others

N/A

Certification

EMC

FCC (USA) FCC Part 15, Subpart B class ACE (Europe) EN55022, EN55024VCCI (Japan) V-3 (CISPR22)KCC

(Korea) :KN22, KN24BSMI (Taiwan) : CNS13438 (CISPR22)C-Tick (Australia) : AS/NZS3548 (CISPR22)

CCC(China) :GB 9254-2008, GB 17625.1-2003

Environment

N/A

Safety

UL (USA) : UL 60950-1CSA (Canada) : CSA C22.2 No. 60950-1 TUV (Germany) : EN60950-1NEMKO

(Norway) : EN60950-1 KC (Korea) : K60950-1 CCC (China) : GB 4943-2001PSB (Singapore) :

IEC60950-1GOST (Russia) : IEC60950-1, EN55022SIQ (Slovenia) : IEC60950-1, EN55022PCBC (Poland) :

IEC60590-1, EN55022NOM (Mexico) : NOM-019-SCFI-1993IRAM (Argentina) :IEC60950-1SASO (Saudi

Arabia) : IEC60950-1

Accessory

Included

Quick Setup Guide, Warranty Card, Application CD, Power Cord, Remote Controller, Batteries

Optional

Mount

N/A  
Specialty  
N/A  
Stand  
N/A