
Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Nazwa	Projektor Sim2 D35 EOL
-------	-------------------------------

Cena	0,00 zł
------	----------------

Producent	Sim2
-----------	-------------

OPIS PRODUKTU

LIGHT ENGINE

DLP® type

1 chip DMD (HD2+ DarkChip2™)

Resolution

1280 x 720 pixels

Lens

High quality, high resolution optics with both motorized zoom and focus adj.

Lamp power & life time*

150W 6000 hours

INSTALLATION

Throw ratio

1.8 - 2.4:1 (16:9 mode)

Lens shift

V+/-50%

Digital keystone adjustment

V+/-18°; H+/-10°

Picture size (inches diagonal)

50-250

Aspect ratio

4:3, 16:9, Anamorphic, LetterBox, panoramic, pixel to pixel + 3 custom-user adjustments

ELECTRONICS

Horiz. & Vert. scan freq.

15-80kHz - 48-100Hz

Video standards (autom. selected)

PAL B, G, H, I, M, N, 60; SECAM; NTSC 3,58 & 4,43

HDTV ATSC standards and graphic resolutions

USA 480p, 720p, 1080i, 60Hz; EU 576p, 1080i 50Hz.; VGA, SVGA, XGA, SXGA, UXGA (60-85 Hz)

On-board video processing Contrast ratio (Full ON/ Full OFF)

>3200:1

Color temperature

3 preset color temp. selectable by OSD + 1 user adjust.

Special adjustments

noise reduction, overscan

INPUTS/OUTPUTS

Analog

1 x Composite Video (RCA)

1 x S-Video (mini Din 4 pin)

1 x RGBs/YCrCb (4x RCA)

1 x RGBHV (D-Sub 15 pin)

1 x RS232 (D-Sub 9 pin)

Digital

1 x HDMI™-HDCP

Miscellaneous

1 x OUT digital audio (Toslink)

2 x OUT 12V 100mA on Jack connectors

GENERAL SPECIFICATIONS

Software control

upgradable via RS232 serial interface

Power consumption

200W max

Mains voltage range

100-240Vac ±10% (48/62Hz)

Weight

5.0Kg (11 lbs)

Dimensions (WxHxD)

352x174x318 mm (13.9"x6.85"x12.5")

ACCESSORIES

Supplied

Installation and User Manual

AC power cords (EU, UK& USA) 6.6 ft (2m)

Remote control and batteries

The DLP® logo and DLP® medallion are trademarks of Texas Instruments.

(*) Lamp life: the hours quoted have been measured in a lab under strict test conditions. Lamp life varies depending on usage conditions and the surrounding environment. The measured lamp life cannot be guaranteed and is not protected by warranty