

---

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl

---



Nazwa	<b>Projektor Sim2 DOMINO 30H EOL</b>
Cena	<b>0,00 zł</b>
Producent	<b>Sim2</b>

---

## OPIS PRODUKTU

### LIGHT ENGINE

DLP™ Type

Proprietary sealed optical Engine based on 1 HD2+ DMD™ Chip.

Resolution

1280x720 pixels

Lens

High quality, high resolution optics with both motorised zoom and focus adjustments

Throw ratio(16:9 mode)

1.8 - 2.4:1

Throw ratio (4:3 mode)

2.4 - 3.0:1

Lamp power consumption & life time

120W, 6000 hours\*

### INSTALLATION

Optical keystone adjustment

+/-8°

Digital keystone adjustment

+/-18° vertical, +/-12° horizontal

Picture size

50-300 inches diagonal.

Aspect ratio

4:3, 16:9, anamorphic, letterbox, panoramic pixel to pixel + 3 custom-user adjustments

### ELECTRONICS

Horiz. Scan freq.

15-80KHz (max horizontal freq. corresponding to UXGA, 60Hz)

Vert. Scan freq.

48-100Hz

Video standard & graphic resolutions

PAL B,G,H,I,M,N,60, SECAM, NTSC 3.58 &4.43 automatically selected; HDTV: ATSC (480p, 720p, 1080i);  
VGA, SVGA, XGA, SXGA, UXGA

DCDi™ by Faroudja

built-in

Contrast Ratio (full On / full Off)

> 2800:1

Colour Temperature

3 preset colour temperatures + 1 user adjustment with separate adjustments for high and low light

INPUTS/OUTPUTS

Analog

1 x Composite video via RCA connectors

1 x S-VHS via mini Din 4 pin

1 x RGBHV via Dsub 15 (PC input)

1 x RGBS/YCrCbS via 4xRCA connectors

Digital

1 x HDMI™-HDCP

1 x optical S/PDIF audio output from HDMI™

1 x DVI+HDCP via DVI-HDMI™ cable

Miscellaneous

1 x RS232 on Dsub 9 pins connector

2 x OUT 12 V 100 mA

GENERAL SPECIFICATIONS

Control

Software can be upgraded via RS232 serial interface

Power Consumption

180 W max

Mains voltage range

120 - 240 Vac, +/- 10%

Mains frequency range

48/62 Hz

Cabinet dimensions (W x H x D)

350 x 167 x 318mm (13,8" x 6,6" x 12,5")

Weight

5.0 Kg. (11 lbs)

CABINET COLOURS

Cabinet Colours

Black Shadow or White Evolution

CERTIFICATIONS

Safety

In compliance with EN 60950/UL 60950

Emission

In compliance with EN 55022 class B/150KHz - 30MHz

Recyclable packaging

ACCESSORIES

Supplied

AC power cords (EU,UK, and USA) length 3m

User standard remote control with batteries

