
Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Nazwa	Projektor SIM2 Grand Cinema Lumis Plus T1
-------	--

Cena	173 490,00 zł
------	----------------------

Producent	Sim2
-----------	-------------

OPIS PRODUKTU

LIGHT ENGINE

DLP® Type

3 Chip DMDs 0,95" 1080p DC4

Resolution

1920x1080 pixels

Lens

High quality, high resolution improved optics for higher contrast and better black level with motorized zoom and focus adj.

Special features

NEW 330W dimmable high efficiency long-life lamp (up to 5,000 hours)

PureAction 3D technology with triple flash

PureAction 2D for fast action materials

SIM2 DynamicBlack™ Technology enhanced solution (in 2D mode only)

Contrast ratio (Full ON/ Full OFF)

>30,000:1 with DynamicBlack™ Technology (in 2D mode only)

Lamp power

330W dimmable with lamp life up to 5000 hours

Brightness(**)

4300 ANSI lumens for High Brightness lens

3500 ANSI lumens for Extended Contrast LENS

Lamp life expectancy(*)

up to 5,000 hours

INSTALLATION

Throw ratio standard lens

1.82-2.48:1 (type T2)

Throw ratio optional lenses

1.37-1.66:1 (typ. T1)

2.6-3.9:1 (typ. T3)

Optical shift

Vertical up to +50%, down -10% max. from screen center (based on image height)

Digital keystone adjustment

+/-18°

Picture size (inches diagonal)

50-300

Aspect ratio

4:3, 16:9 Anamorphic, LetterBox, Panoramic, Pixel to Pixel + 3 custom-user adjustments

ELECTRONICS

Horizontal & vertical scan freq.

15-80kHz/48-144Hz

SDTV

PAL (B,G,H,I,M,N,60); SECAM; NTSC autom. selected

HDTV

480p, 720p 50/60, 1080i 50/60, 1080p 24/50/60 + 576p

PC graphic standard

VGA, SVGA, XGA, SXGA, UXGA, WUXGA 10 bit Full Channel Signal Board Video Processing

INPUTS/OUTPUTS

Digital

2 x HDMI-HDCP (v.1.4 with Deep Color)

Analog

1x Composite Video

1 x Graphic RGBVH (VGA-UXGA) (D-sub 15 pin)

1 x Component - Analog YPbPr/RGBs/RGBHV (RCA)

Control

3D Sync out

1 x RS232 (D-sub 9 pin)

1 x USB (B type)

Miscellaneous

3 x 12V 100mA output (via Jack)

GENERAL SPECIFICATIONS

Software control

upgradable via RS232, serial interface or USB

Mains voltage range

100-240 +/-10% (48/62 Hz)

Projector Weight

11 Kg. or 24.3 lbs

Projector dimensions (WxHxD)

459 x 210 x 455 mm (18.1"x 8.3" x 17.9")

ACCESSORIES

Supplied

Installation and User Manual

AC power cords (2m - 6.6 ft)

Backlit remote control and batteries

Live Colors Calibration software 2.0

Premium SIM2 RF VISUS Active Glasses (4 pcs.)

Emitter

Optional

Projector ceiling bracket

Anamorphic lens systems (fixed or motorized)

Additional VISUS active glasses