

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Nazwa **Projektor Sim2 HT300 E EOL**

Cena **0,00 zł**

Producent **Sim2**

## OPIS PRODUKTU

Light Engine

DLP™ Type

1 chip DMD HD2+ DarkChip3™

Resolution

1280 x 720 pixels

Lens

High Quality, high resolution improved optics for higher contrast and better black level with both motorized zoom and focus adj.

Lamp power & life time\*

120W 8000 hours

Installation

Throw ratio

1,8-2,4:1

Lens shift

V+/-8°

Digital keystone adjustment

V+/-18°; H+/-10°

Picture size (inches diagonal)

50-250

Aspect ratio

16:9 Anamorphic, LetterBox, panoramic, pixel to pixel + 3 custom-user adjustments

Electronics

Horizontal & vertical scan freq.

15-80kHz/48-100Hz (freq. Max H = UXGA 60Hz)

Video signals compatibility

PAL (B,G,H,I,M,N,60); SECAM; NTSC 3,58; NTSC 4,43 automatically selected,+ 1080i 50Hz

HDTV: ATSC (480p, 720p, 1080i); 576p PC graphic standard: VGA, SVGA, XGA, SXGA, UXGA (1600x1200 60Hz)

DCDi™ by Faroudja

FLI2310

Contrast ratio (Full ON/ Full OFF)

>3500:1

Color temperature

36 preset color temperatures selectable by OSD

Special adjustments

noise reduction, fleshtone regulation, overscan, Live Colors Management (LCM) and Gamma adjustments

Intelligent picture memory functions

24 - 3 for each input.

Inputs/Outputs

Analog

1 x Composite Video (RCA)

1x S-Video (mini Din 4 pin)

1 x RGBs/YCrCb (4x RCA)

1 x RGBHV (D-Sub 15 pin)

Digital

1 x HDMI™ - - HDCP

1 x OUT Digital Audio (Toslink)

1 x DVI (DVI-D)

Control

1 x RS232 (D-Sub 9 pin)

Miscellaneous

1 x OUT 12V 100mA (via Jack) active when the projector is ON

1 x OUT 12V 100mA (via Jack) active when 16:9 format is selected

General Specifications

Software control

upgradable via RS232 serial interface

Power consumption

170W max

Mains voltage range

120-240Vac ±10% (48/62Hz)

Weight

5.8Kg (12.8 lbs)

Dimensions (WxHxD)

350x173x318mm (13.8"x6.8"x12.5")

Accessories

Supplied

Installation and User Manual

AC power cords (EU, UK ed USA) 2m (6.6 ft)

Backlit remote control and batteries

Optional

HT BRKT floor and ceiling mounting bracket

HTR01 universal remote control

Cabinet Colour

Standard

Gun Metal