

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Nazwa **Projektor Sim2 HT305 E EOL**

Cena **0,00 zł**

Producent **Sim2**

OPIS PRODUKTU

Light Engine

DLP® type

1 chip DMD (HD2+ DarkChip3™)

Resolution

1280 x 720 pixels

Lens

High quality, high resolution improved optics for higher contrast and black level with both motorized zoom and focus adj.

Lamp power & life time*

150W 6000 hours

Installation

Throw ratio

1.8 - 2.4:1 (16:9 mode)

Lens shift

V+/-50%

Digital keystone adjustment

V+/-18°; H+/-10°

Picture size (inches diagonal)

50-250

Aspect ratio

4:3, 16:9 Anamorphic, LetterBox, panoramic, pixel to pixel + 3 custom-user adjustments

Electronics

Horiz. & Vert. scan freq.

15-80kHz - 48-100Hz

Video standards (autom. selected)

PAL B, G, H, I, M, N, 60; SECAM; NTSC 3,58 & 4,43

HDTV ATSC standards and graphic resolutions

USA 480p, 720p, 1080i, 60Hz; EU 576p, 1080i 50Hz.; VGA, SVGA, XGA, SXGA, UXGA (60 - 85 Hz)

On-board video processing Contrast ratio (Full ON/ Full OFF)

>3500:1

Special adjustments

noise reduction, overscan, Live Colors Management

Inputs/Outputs

Analog

1 x Composite Video (RCA)

1 x S-Video (mini Din 4 pin)

1 x RGBs/YCrCb (4x RCA)

1 x RGBHV (D-Sub 15 pin)

Control

1 x RS232 (D-Sub 9 pin)

Digital

1 x HDMI™-HDCP

1 x OUT digital audio (Toslink)

Miscellaneous

2 x OUT 12V 100mA on Jack connectors

General Specifications

Software control

upgradable via RS232 serial interface

Power consumption & Mains voltage range

200W max; 100-240Vac ±10% (48/62Hz)

Weight

5.8Kg (12.8 lbs)

Dimensions (WxHxD)

350x173x318 mm (13.8"x6.8"x12.5")

Accessories

Supplied

Installation and User Manual

AC power cords (EU, UK & USA) 6.6 ft (2m)

Backlit Remote control and batteries