
Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Nazwa	Projektor Sim2 SUPERLUMIS
Cena	0,00 zł
Producent	Sim2

OPIS PRODUKTU

DISPLAY

DLP® Type

3 Chip DMDs 0,95" 1080p DC4

Resolution

1920x1080 pixels

Lens

High quality selected optic glass lenses

Special features

PureAction 3D technology

Triple flash genuine 144hz cinema reproduction

PureAction 2D for fast action materials

Puremovie 2D

SIM2 DynamicBlack™ Technology enhanced solution (in 2D mode only)

Contrast ratio (Full ON/ Full OFF)

up to 30,000:1 with DynamicBlack™ Technology and EC lens type (in 2D mode only)

Lamp power

350W (dimmable)

Brightness(**)

up to 5000 Ansi Lumens (adjustable) with HB lens

up to 3800 ANSI Lumens (adjustable) with EC lens type

Lamp life expectancy(*)

2000 hours typical in standard power mode; 3000 hours in ECO mode

INSTALLATION

Lens type

High Brightness (HB)

Extended Contrast (EC)

Throw ratio standard lens

1.82-2.48:1 (type T2)

Throw ratio optional lenses

1.37-1.66:1 (typ. T1)

2.6-3.9:1 (typ. T3)

Optical shift

Motorized, vertical up to +50%, down -10% max. from screen center (based on image height)

Digital keystone adjustment

Vertical, +/-18°

Picture size (inches diagonal)

50-300

Aspect ratio

4:3, 16:9 Anamorphic, LetterBox, Panoramic, Pixel to Pixel + 3 custom-user adjustments

ELECTRONICS AND CONNECTIVITY

Horizontal & vertical scan freq.

15-80kHz/24-144Hz

SDTV

PAL (B,G,H,I,M,N,60); SECAM; NTSC autom. selected

HDTV

480p, 720p 50/60, 1080i 50/60, 1080p 24/50/60 + 576p

PC graphic standard

VGA, SVGA, XGA, SXGA, UXGA, WUXGA 10 bit Full Channel Signal Board Video Processing

INPUTS/OUTPUTS

Digital

2 x HDMI-HDCP vers. 1.4a (v.1.4 with Deep Color)

Analog

1x Composite Video

1 x Graphic RGBVH (VGA-UXGA) (D-sub 15 pin)

1 x Component - Analog YPbPr/RGBs/RGBHV (RCA)

Control

3D Sync out

1 x RS232 (D-sub 9 pin)

1 x USB (B type)

Miscellaneous

3 x 12V 100mA output (via Jack)

GENERAL SPECIFICATIONS

Software control

upgradable via RS232, serial interface or USB

Mains voltage range

100-240 +/-10% (48/62 Hz)

Projector Weight

11 Kg. or 24.3 lbs

Projector dimensions (WxHxD)

458x210x455 mm (18"x8.3"x17.9")

ACCESSORIES

Supplied

Installation and User Manual

AC power cords (2m - 6.6 ft)

Backlit remote control and batteries

Live Colors Calibration software 2.0

Premium SIM2 VISUS Active Glasses (4 pcs.)

Emitter

Optional

Projector ceiling bracket

Anamorphic lens systems (fixed or motorized)

Additional VISUS active glasses

(*) Lamp life: the hours quoted have been measured in a lab under ideal test conditions. Lamp life varies depending on usage conditions and the surrounding environment. This is an average value that cannot be guaranteed and is not protected by warranty.

(**)ANSI Lumen Specification: This is the typical projector brightness specification found in most sales literature. This measurement allows for direct comparison with other manufacturer's projectors.

Measurements are taken in a totally dark test room with T3 type lens (wide angle zoom settings), brand new lamp at full power, lamp's native white color temperature, internal test pattern (full white) and in compliance with ANSI IT7.228-1997 specification.

Due to constant product development, specifications are subject to change without notice.