
Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



SONY

Nazwa	Monitor LCD Sony LMD-2041W
-------	----------------------------

Cena	0,00 zł
------	---------

Producent	Sony
-----------	------

OPIS PRODUKTU

Technical Specifications

Picture Performance

Panel

a-Si TFT Active Matrix LCD

Picture Size (Diagonal)

508 mm

20 inches

Effective Picture Size (H x V)

442.8 x 249.1 mm

17 1/2 x 9 7/8 inches

Resolution (H x V)

1600 x 900 pixels

Aspect

16:9

Pixel Efficiency

0.9999

Backlight

LED

Colors

Approx.16.7 million colors

Viewing Angle (Panel Specification)

89°/89°/89°/89° (typical) (up/down/left/right contrast 10:1)

Normal Scan

0% scan

Over Scan

5% over scan

Input

Composite Input

BNC (x1), 1 Vp-p ±3dB, sync negative

SDI Input

BNC (x2)

HDMI Input

HDMI (x1) (HDCP correspondence)

Audio Input

Stereo mini jack (x1), -5 dBu 47 k Ω or higher

Parallel Remote

Modular connector 8-pin (x1)

(Pin-assignable)

Serial Remote (LAN)

RJ-45 (x1) (Ethernet, 10BASE-T/100BASE-TX)

DC Input

XLR-type 4-pin (male) (x1), 12V DC (output impedance 0.05 Ω or less)

Output

Composite Output

BNC (x1), Loop-through, with 75 Ω automatic terminal function

SDI Output

BNC (x1), output signal amplitude: 800 mVp-p \pm 10%, output impedance: 75 Ω unbalanced

Audio Monitor Output

Stereo mini jack (x1)

Speaker (Built-in) Output

1.0 W (Monaural)

Headphone Output

Stereo mini jack (x1)

General

Power Requirements

100 V to 240 V AC, 0.8 A to 0.4 A, 50/60 Hz

12 V DC, 4.4 A

Power Consumption

Approx. 66 W (max.)

Inrush Current

(1) Maximum possible inrush current at initial switch-on (Voltage changes caused by manual switching):

57 A peak, 0.3 A r.m.s. (240V AC)

(2) Inrush current after a mains interruption of five seconds (Voltage changes caused at zero-crossing):

46 A peak, 0.2 A r.m.s. (240V AC)

Operating Temperature

0°C to 35°C (Recommended: 20°C to 30°C)

32°F to 95°F (Recommended: 68°F to 86°F)

Operating Humidity

30% to 85% (no condensation)

Storage/Transport Temperature

-20°C to +60°C

-4°F to +140°F

Storage/Transport Humidity

0% to 90%

Operating/Storage/Transport Pressure

700 hPa to 1060 hPa

Dimensions (W x H x D) [*1]

482.6 x 314.8 x 100.2 mm

482.6 x 332.8 x 171.4 mm (with supplied monitor feet)

482.6 x 452.0 x 269.9 mm (with SU-561 optional stand)

19 x 12 1/2 x 4 inches

19 x 13 1/8 x 6 3/4 inches (with supplied monitor feet)

19 x 17 7/8 x 10 3/4 inches (with SU-561 optional stand)

Mass

Approx. 6.7 kg (without a monitor stand)
Approx. 14 lb 12 oz (without a monitor stand)
Approx. 6.9 kg (with supplied monitor feet)
Approx. 15 lb 3 oz (with supplied monitor feet)
Approx. 8.8 kg (with monitor stand SU-561)
Approx. 19 lb 6 oz (with monitor stand SU-561)

Supplied Accessories

AC power cord (1)

AC plug holder (1)

Mounting bracket (2) (including 8 screws)

Monitor foot (2) (including 6 screws)

Operating Instructions (1)

CD-ROM (1)

Using the CD-ROM Manual (1)

Optional Accessories

SU-561 Monitor Stand

Notes

Note

[*1] The values for dimensions are approximate.