
Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl

SONY

Nazwa	Monitor referencyjny LCD Sony PVM-L1700
-------	---

Cena	0,00 zł
------	---------

Producent	Sony
-----------	------

OPIS PRODUKTU

Specyfikacja techniczna

Picture Performance

Panel

a-Si TFT Active Matrix LCD

Picture Size (Diagonal)

419.0 mm

Picture Size (Diagonal)

16 1/2 inches

Effective Picture Size (H x V)

365.8 x 205.7 mm

Effective Picture Size (H x V)

14 1/2 x 8 1/8 inches

Resolution (H x V)

1920 x 1080 pixels (Full HD)

Aspect

16:9

Pixel Efficiency

0.9999

Backlight

CCFL

Panel Drive

RGB 10-bit

Panel Frame Rate

96 Hz, 100 Hz, 120 Hz

Viewing Angle (Panel Specification)

89°/89°/89°/89° (typical) (up/down/left/right contrast 10:1)

Normal Scan

0% scan

Native Scan

Mapping the pixels of the signal to the panel to one-to-one mode, or displaying an SD signal of nonsquare pixels (the number of H pixels of the signal system is 720 or 1440) or a 640 × 480 SD signal of HDMI video by scaling processing of doubling for the V direction and correct aspect ratio for the H direction and also optimizing and sidplaying a picture by modifying the aperture coefficient value, filter coefficient value, etc.

Under Scan

3% under scan

Over Scan

Mask of 5% over scan portion in the normal scan

Color Temperature

D65, D93, User

Standard Luminance

100 cd/m² (Preset1 to Preset5)

Standard Luminance

(1.0 Vp-p reference signal, 100% white signal input)

Color Space (Color Gamut)

ITU-R BT.709, EBU, SMPTE-C, L1700 Native (The PVM-L2300 individual chromaticity points. The widest color space setting of the signal is reproduced by the PVML3200. R (x = 0.643, y = 0.334)/G (x = 0.212, y = 0.673)/B (x = 0.150, y = 0.060) (typical))

Warm-up Time

Approx. 30 minutes

Input

HDMI Input

HDMI (x1) (HDCP correspondence, Deep Color correspondence)

DVI-D Input

DVI-D (x1) (HDCP correspondence)

Option Port

Four (4) ports

Parallel Remote

D-sub 9-pin (female) (x1)

Serial Remote (LAN)

RJ-45 (x1) (Ethernet, 10BASE-T/100BASE-TX)

Option A Input

Mini-DIN 8-pin (female) (x1)

Option B Input

USB (Type A) (x1) (used for future expansion)

DC Input

XLR-type 3-pin (male) (x1), 24V DC (output impedance 0.05 Ω or less)

Output

DC 5 V Output

Circle 4-pin (female) (x1)

General

Power Requirements

100 V to 240 V AC, 1.2 A to 0.5 A, 50/60 Hz

Power Requirements

24V to 28V DC, 4.6A to 4.06 A

Power Consumption

Approx. 110 W (AC power supply), 100 W (DC power supply) (max.)

Power Consumption

Approx. 90 W (AC power supply), 80 W (DC power supply) (with BKM-243HS, average power consumption in the default status)

Inrush Current

(1) Power ON, current probe method:

Inrush Current

20 A (100 V), 53 A (240V)

Inrush Current

(2) Hot switching inrush current, measured in accordance with European standard EN55103-1:

Inrush Current

13 A (230 V)

Operating Temperature

0°C to 35°C (Recommended: 20°C to 30°C)

Operating Temperature

32°F to 95°F (Recommended: 68°F to 86°F)

Operating Humidity

0% to 90% (no condensation)

Storage/Transport Temperature

-20°C to +60°C

Storage/Transport Temperature

-4°F to +140°F

Storage/Transport Humidity

0% to 90%

Operating/Storage/Transport Pressure

700 hPa to 1060 hPa

Dimensions (W x H x D) [*1]

436 x 265.8 x 278.6 mm

Dimensions (W x H x D) [*1]

17 1/4 x 10 1/2 x 11 inches

Mass

Approx. 11.0 kg

Mass

Approx. 24 lb 4 oz

Supplied Accessories

AC power cord (1)

Supplied Accessories

AC plug holder (1)

Supplied Accessories

Rack mount bracket (Left, right, each 1)

Supplied Accessories

Rack mount attachment screws (6)

Supplied Accessories

Connection Cable for Color Temperature Probe (1)

Supplied Accessories

Operation Manual (Japanese, English, each 1)

Supplied Accessories

CD-ROM (1)

Supplied Accessories

Using the CD-ROM Manual (1)

Optional Accessories

BKM-16R Monitor Control Unit

Optional Accessories

BKM-39H Controller Attachment Stand

Optional Accessories

SMF-700 Monitor Interface Cable

Optional Accessories

BKM-220D SDI 4:2:2 Input Adaptor (with serial number 2100001 or higher)

Optional Accessories

BKM-227W NTSC/PAL Input Adaptor

Optional Accessories

BKM-229X Analog Component Input Adaptor (with serial number 2200001 or higher)

Optional Accessories

BKM-243HS HD/D1-SDI Input Adaptor (with serial number 2108355 or higher)

Optional Accessories

BKM-244CC HD/SD-SDI Closed Caption Adaptor

Optional Accessories

BKM-250TG 3G/HD/SD-SDI Input Adaptor (with serial number 7100001 or higher)

Notes

Note

[*1] The values for dimensions are approximate.