
Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl

SONY

Nazwa	Monitor Sony LMD-2051W
-------	------------------------

Cena	0,00 zł
------	---------

Producent	Sony
-----------	------



OPIS PRODUKTU

Specyfikacja techniczna

Picture Performance

Panel

a-Si TFT Active Matrix LCD

Picture Size (Diagonal)

511.1 mm

Picture Size (Diagonal)

20 1/8 inches

Effective Picture Size (H x V)

433.4 x 270.9 mm

Effective Picture Size (H x V)

17 1/8 x 10 3/4 inches

Resolution (H x V)

1680 x 1050 pixels (WSXGA)

Aspect

16:10

Pixel Efficiency

0.9999

Backlight

CCFL

Colors

Approx.16.7 million colors

Viewing Angle (Panel Specification)

89°/89°/89°/89° (typical) (up/down/left/right contrast 10:1)
Normal Scan
0% scan
Over Scan
5% over scan
Input
Composite Input
BNC (x1), 1 Vp-p ±3dB sync negative
Y/C Input
Mini-DIN 4-pin (x1)
Y/C Input
Y: 1 Vp-p ± 3dB sync negative
Y/C Input
C: 0.286 Vp-p ± 3dB (NTSC burst signal level), 0.3 Vp-p ± 3dB (PAL burst signal level)
RGB, Component Input
BNC (x3)
RGB, Component Input
RGB: 0.7 Vp-p ± 3dB (Sync On Green, 0.3 Vp-p sync negative)
RGB, Component Input
Component: 0.7 Vp-p ± 3dB
DVI-D Input
DVI-D (x1)
DVI-D Input
TMDS single link
HD15 Input
D-sub 15-pin (x1),
HD15 Input
R/G/B: 0.7 Vp-p sync positive (Sync On Green, 0.3 Vp-p sync negative)
HD15 Input
Sync : Total level (polarity free, H/V separate sync)
HD15 Input
Plug & Play function : corresponds to DDC2B
Audio Input
Phono jack (x2) -5 dBu 47 kΩ or higher
External Sync Input
BNC (x1)
External Sync Input
0.3 to 4.0 Vp-p ±bipolarity ternary or negative polarity binary
Option Port
Two (2) ports
Option Port
Signal format: H: 15 kHz to 45 kHz, V: 48 Hz to 60 Hz
Parallel Remote
Modular connector 8-pin (x1)
Parallel Remote
(Pin-assignable)
Serial Remote (LAN)
D-sub 9-pin (RS-232C) (x1), RJ-45 (x1) (Ethernet, 10BASE-T/100BASE-TX)
DC Input
XLR-type 4-pin (male) (x1), 24V DC (output impedance 0.05 Ω or less)
Output
Composite Output
BNC (x1), Loop-through, with 75 Ω automatic terminal function
Y/C Output
4-pin mini-DIN (x1), Loop-through, with 75 Ω automatic terminal function

RGB, Component Output

BNC (x3), Loop-through, with 75 Ω automatic terminal function

External Sync Output

BNC (x1), Loop-through, with 75 Ω automatic terminal function

Audio Monitor Output

Phono jack (x2)

Speaker (Built-in) Output

1.0 W + 1.0 W (stereo)

General

Power Requirements

100 V to 240 V AC, 0.8 A to 0.4 A, 50/60 Hz

Power Requirements

24 V DC, 3.3 A

Power Consumption

Approx. 95 W (max.) (with 2 x BKM-229X)

Inrush Current

(1) Power ON, current probe method:

Inrush Current

16 A (100 V), 34 A (240 V)

Inrush Current

(2) Hot switching inrush current,

Inrush Current

measured in accordance with

Inrush Current

European standard EN55103-1: 36A (230 V)

Operating Temperature

0°C to 35°C (Recommended: 20°C to 30°C)

Operating Temperature

32°F to 95°F (Recommended: 68°F to 86°F)

Operating Humidity

30% to 85% (no condensation)

Storage/Transport Temperature

-20°C to +60°C

Storage/Transport Temperature

-4°F to +140°F

Storage/Transport Humidity

0% to 90%

Operating/Storage/Transport Pressure

700 hPa to 1060 hPa

Dimensions (W x H x D) [*1]

518.5 x 328.7 x 104.7 mm (without a stand)

Dimensions (W x H x D) [*1]

518.5 x 468.4 x 269.9 mm (with a supplied stand)

Dimensions (W x H x D) [*1]

20 1/2 x 13 x 4 1/8 inches (without a stand)

Dimensions (W x H x D) [*1]

20 1/2 x 18 1/2 x 10 3/4 inches (with a supplied stand)

Mass (with options)

Approx. 10.5 kg (when 2x BKM-229X installed)

Mass (with options)

Approx. 23 lb 2 oz (when 2x BKM-229X installed)

Mass

Approx. 10.1 kg (when no input adaptor installed)

Mass

Approx. 22 lb 4 oz (when no input adaptor installed)

Supplied Accessories

AC power cord (1)

Supplied Accessories

AC plug holder (1)

Supplied Accessories

Operating Instructions (1)

Supplied Accessories

CD-ROM (1)

Supplied Accessories

Using the CD-ROM Manual (1)

Supplied Accessories

Warranty book (1)

Optional Accessories

BKM-220D SDI 4:2:2 Input Adaptor

Optional Accessories

BKM-243HS HD/D1-SDI Input Adaptor

Optional Accessories

BKM-227W NTSC/PAL Input Adaptor

Optional Accessories

BKM-229X Analog Component Input Adaptor

Optional Accessories

BKM-244CC HD/SD-SDI Closed Caption Adaptor

Optional Accessories

BKM-250TG 3G/HD/SD-SDI Input Adaptor

Optional Accessories

MB-529 Mounting Bracket

Notes

Note

[*1] The values for dimensions are approximate.