

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



mercado actual

# SONY

Nazwa **Projektor Sony VPL-DX146**

Cena **2 460,00 zł**

Producent **Sony**

## OPIS PRODUKTU

### Technical Specifications

Display system

Display system

3 LCD system

Display device

Size of effective display area

0.63" (16.0 mm)

Number of pixels

XGA (1024 x 768)

Aspect ratio

4:3

Projection lens

Focus

Manual

Zoom > Powered / Manual

Manual

Zoom > Ratio

Approx. 1.3 x

Throw ratio

1.36:1 to 1.77:1

Light source

Type

\*1 lamp

Wattage

210 W type

Recommended lamp replacement time\*2

Lamp mode: High

3000 H

Lamp mode: Standard

5000 H

Lamp mode: Low

7000 H

Filter cleaning / replacement cycle\*2 (Max.)

Filter cleaning / replacement cycle\*2 (Max.)

1000 H (cleaning)

Screen size

Screen size

30" to 300"

(0.76 m to 7.62 m)

Light output

Lamp mode: High

3200 lm

Lamp mode: Standard

2300 lm\*3

Lamp mode: Low

1900 lm\*3

Color light output

Lamp mode: High

3200 lm

Lamp mode: Standard

2300 lm\*3

Lamp mode: Low

1900 lm\*3

Contrast ratio (full white / full black)\*4

Contrast ratio (full white / full black)\*4

2500:1

Input

Composite video > Pin Jack

1

Computer > Mini D-sub 15-pin

1

HDMI (HDCP)

1

Audio > Stereo mini jack

1

I/O, Control, Others

LAN > RJ-45, 10BASE-T/100BASE-TX

1

USB > Type A

1

USB > Type B

1

Wireless

IFU-WLM3(Supply)\*5

Speaker

Speaker

1 W x 1 (monaural)

Keystone correction (Max.)\*6

Vertical

+/- 30°

Power requirements

Power requirements

AC 100 V to 240 V

3.0 A to 1.2 A, 50/60 Hz

Power consumption

AC 100 V to 120 V > Lamp mode: High

291 W

AC 100 V to 120 V > Lamp mode: Standard

229 W\*3

AC 100 V to 120 V > Lamp mode: Low

199 W\*3

AC 220 V to 240 V > Lamp mode: High

279 W

AC 220 V to 240 V > Lamp mode: Standard

223 W\*3

AC 220 V to 240 V > Lamp mode: Low

194 W\*3

Standby mode power consumption

AC 100 V to 120 V > Standard

5.7 W

AC 100 V to 120 V > Low

0.4 W

AC 220 V to 240 V > Standard

5.9 W

AC 220 V to 240 V > Low

0.5.W

Heat dissipation

AC 100 V to 120 V

992 BTU

AC 220 V to 240 V

951 BTU

Dimensions (W x H x D) (without protrusions)

Dimensions (W x H x D) (without protrusions)

315 x 75 x 230.5 mm

12 13/32 x 2 15/16 x 9 1/16 in

Mass

Mass

2.6 kg / 5.8 lb

Supplied accessories

Remote commander

RM-PJ8

Wireless LAN Module

IFU-WLM3

Optional accessories

Replacement lamp

LMP-D213

Wireless LAN Module

IFU-WLM3 (Supply)

Notes

\*1

Ultra high pressure mercury.

\*2

The figures are the expected maintenance time and not guaranteed. They will depend on the environment or how the projector is used.

\*3

The values are estimate.

\*4

This value is average.

\*5

Connect to USB Type-A terminal.

\*6

Depends on resolution.