

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl

SONY



Nazwa **Projektor Sony VPL-VW885ES**

Cena **0,00 zł**

Producent **Sony**

OPIS PRODUKTU

Dane techniczne

Specifications

Features

Full Specifications and Features

,999.991

Where To Buy

Specifications

Features

Size & Weight

DIMENSIONS (W X H X D)

22.06 x 8.78 x 19.53

WEIGHT

Approx. 44 lb (20 kg)

Display

DISPLAY SYSTEM

4K SXRD panel, projection system

DISPLAY RESOLUTION

Computer signal input: Maximum display resolution: 1,920 x 1,080 dots (HDMI Input only)/Video signal

input: 480/60p, 576/50p, 720/60p, 720/50p, 1080/60 i, 1080/50 i, 1080/60p, 1080/50p, 1080/24p, 3840 x

2160/24p, 3840 x 2160/25p, 3840 x 2160/30p, 3840 x 2160/50p, 3840 x 2160/60p, 4096 x 2160/24p,

4096 x 2160/25p, 4096 x 2160/30p, 4096 x 2160/50p, 4096 x 2160/60p

LIGHT SOURCE

Laser diode

General Features

CONTRAST RATIO

∞: 1 (Dynamic Contrast)

EFFECTIVE IMAGER SIZE

0.74" x 3

EFFECTIVE PIXELS

26,542,080 (4096 x 2160 x 3) pixels

PROJECTION LENS SHIFT

Vertical: +85% -80% Horizontal: +/-31%

SCREEN SIZE

60" to 300"/1,524 mm to 7,620 mm (diag.)

Hardware

PROJECTION LENS ZOOM / FOCUS

Powered (Approx. x2.06)

Interface

INPUT AND OUTPUT TERMINALS

HDMI (2 INPUTS)*1 - Digital RGB/Y Pb/Cb Pr/Cr, IR IN - Minijack, LAN - RJ45, 10Base-T/100BASE-TX,

REMOTE - RS-232C, D-sub 9-pin (male), TRIGGER (2 INPUTS) - Minijack, DC 12 V Max. 100 mA, USB - DC 5 V, Max. 500 mA

Operating Conditions

OPERATING TEMPERATURE / HUMIDITY

41 °F to 95 °F (5 °C to 35 °C)/20% to 80% (no condensation)

STORAGE TEMPERATURE / HUMIDITY

14°F to +140°F (-10°C to +60°C)/20% to 80% (no condensation)

Power

ACOUSTIC NOISE

24 dB*2

POWER REQUIREMENT

AC 100 V to 240 V, 4.3 A to 1.8 A, 50/60 Hz

POWER CONSUMPTION

430 W

Video Features

LIGHT OUTPUT

2000 lm

COLOR LIGHT OUTPUT

2000 lm

Eco and energy saving

POWER CONSUMPTION (STANDBY MODE)

0.4 W (When "Remote Start" is set to "Off")

POWER CONSUMPTION (NETWORKED STANDBY MODE)

1.0 W (LAN) (When "Remote Start" is set to "On") When a LAN terminal is not connected, it becomes a low power consumption mode (0.5 W).

STANDBY MODE ACTIVATED

After about ten minutes

Footnotes

*1

Both HDMI inputs are compatible with HDCP 2.2.

*2

This value is approximate. Depends on the projector setting condition and usage environment.

What's In The Box

Remote Control (RM-PJ24)

Size AA (R6) manganese batteries (2)

AC Power Cord (1), Lens Cap (1)

Operating Instructions (CD-ROM)

Quick Reference Manual

Safety Regulations (1)

CECHY PRODUKTU

Model/Seria

VPL-VW885ES

Technologia	SXRD
Rozdzielczość (Podstawowa)	4K
Format Obrazu	1.89:1
Jasność	2000
Kontrast (...:1)	999999999999
Źródło Światła	LASER
Żywotność Źródła Światła (Ilość Godzin)	20000
Wsp. Powiększenia/Rzutu (Throw Ratio) Minimalny (...:1)	1.38
Wsp. Powiększenia/Rzutu (Throw Ratio) Maksymalny (...:1)	2.83