

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



**ViewSonic**   
See the difference™

Nazwa

**Cienki klient ViewSonic Raspberry Pi 3  
Thin Client SC-T25**

Cena

**0,00 zł**

Producent

**ViewSonic**

## OPIS PRODUKTU

### SPECIFICATIONS

#### CORE

CPU : Broadcom BCM2837

CPU Processor Speed : 1.2GHz Quad Core Cortex A3

#### GRAPHICS

Chipset : Dual core ViseoCore IV. Multimedia Processor

Resolution : 1920 x 1200 (Max)

#### MEMORY

System : 1GB LPDDR2 450MHz

Storage : External 8GB micros SD

#### CONNECTOR

HDMI : 1 (rev 1.3 &1.4)

USB : USB2.0 x 4

Audio/Composite Video Jack : 3.5mm mini jack (x1)

LAN : RJ45 (x1)

Power : DC In

#### COMMUNICATION

Ethernet LAN : 10/100Mbps

Wireless LAN : 802.11 b/g/n

Physical : 99mm x 61mm x 29.5mm (3.9" x 2.4" x 1.16")

Packaging : 160mmx 110mmx 60mm (6.3"x 4.33" x2.36")

#### REGULATIONS

FCC, ENERGY STAR®, EPEAT Silver, WEEE, RoHS, REACH

SOFTWARE

OS : VTOS( Linux Debian Jessie 8 and Kernel 4.4.7)

Protocols : HDX, VMC, X11, Web, Performance monitor, VDM3.0

Management : ViewSonic Device Manager / ViewSonic configuration tool

POWER

Voltage : 5.1V DC; 2.5A, 13W

Consumption : 13W (typ)

VESA® MOUNT

100mm x 100mm

PACKAGE CONTENTS

SC-T25 Thin Client, Universal power plug pack , power adapter, Quick Start Guide, Compliance information brochure

\*\*Actual content may differ from market to market

OPERATING CONDITIONS

Humidity : 10–90% (non-condensing)

Temperature : 32-104°F (0-40°C)