
Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Nazwa **Monitor 4K Ultra HD ViewSonic CDE6510**

Cena **0,00 zł**

Producent **ViewSonic**

OPIS PRODUKTU

SPECIFICATIONS

LCD PANEL

Panel Size : 65"

Type/ Tech : TFT LCD Module with DLED Backlight

Display Area (mm) : 1428.48 (H) x 803.52 (V)

Aspect Ratio : 16:09

Resolution : 3840x2160 @60Hz

Colors : 1.07B colors

Brightness : 350 nits (typ.)

Contrast Ratio : 4000:1 (typ.)

Response Time : 8 ms

Viewing Angles : H = 178, V = 178 (typ.)

Backlight : DLED

Backlight Life : 30,000 Hours Min.

Hardness : 3H

INPUT

HDMI : x 4

RGB / VGA : x 1

DisplayPort : x 1

Audio : x1 PC audio (3.5 mm)

RS232 : x 1

PC Slot : x 1 (optional VPC12-WPO)

IR : x 1

OUTPUT

RS232 : x 1

IR : x 1

LAN

RJ45 : x 1

USB

Type A : x 1 for 5V/2A

2.0 Type A : x 2 (USB Playback)

3.0 Type A : x 1 (USB Playback)

SPEAKERS

10W x 2

COMPATIBILITY

VGA : 1920 x 1080

DisplayPort : 480i, 480p, 720p, 1080i, 1080p, 4K2K@30Hz

HDMI : 480i, 480p, 720p, 1080i, 1080p, 4K2K@60Hz

POWER

Voltage : 100-240 VAC +/- 10% Wide Range, 50-60Hz +/-3 Hz

Consumption : Normal 165 W, Max 295 W

ERGONOMICS

Wall Mount (VESA®) : 400 x 400mm ; Screw: M6*(10+X) mm. (X=thickness of wall mount plate)

OPERATING CONDITIONS

Temperature (°C) : 5°C to 40°C

Humidity : 20% ~ 80% non-condensing

DIMENSIONS (W X H X D)

Physical (mm / Inch) : 1458.7 x 938.8 x 540 mm / 57.43 x 36.96 x 21.26 in. (with Stand)

Physical W/o Stand (mm / Inch) : 1458.7 x 834.7 x 81.6 mm / 57.43 x 32.86 x 3.21 in. (w/o Stand)

Packaging (mm / Inch) : 1655 x 1078 x 280 mm / 65.16 x 42.44 x 11.02 in

WEIGHT

Net (kg / Lb) : 28.9 kg / 63.71 lbs (with Stand)

Net W/o Stand (kg / Lb) : 24.8 kg / 54.67 lbs (w/o stand)

Gross (kg / Lb) : 34.84 kg / 76.80 lbs

REGULATIONS

Standard : US NRTL with Canada, FCC, Energy star, Mexico CoC and energy , CE, CB, RoHS, ErP, REACH, WEEE, RCM

WHAT'S IN THE BOX?

1. CDE6510 commercial display
2. Remote Control with batteries
3. User manual CD wizard
4. Quick Start Guide
5. Power Cables
6. RS232 cable
7. RS232 daisy chain cable (2.4mm - 2.4mm)
8. IR sensor cable