

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



ViewSonic
See the difference™

Nazwa

**Monitor do ściany video Viewsonic Slim
Narrow Bezel for Seamless Video Wall
Installations CDP4260-L**

Cena

0,00 zł

Producent

ViewSonic

OPIS PRODUKTU

Display

Panel Size

42"

Type/Tech

TFT LCD Module with LED Backlight

Display Area (mm)

930.24(H) x 523.26 (V) (42" diagonal)

Aspect Ratio

16:9

Native Resolution

1920 x 1080

Colors

1.07 Billion

Brightness

450 nits (typ.)

Contrast Ratio

1300:1 Typ.

Response Time

12ms

Viewing Angles

H = 178, V = 178 typ.

Backlight Life

30,000 Hours Typ.

Surface Treatment

Hard coating (3H)

Orientation

Landscape / Portrait

INPUT

HDMI

x1

RGB / VGA

x1

DisplayPort

x1

DVI

x1

Audio

x1 PC audio(3.5 mm), x1 Shared RCA audio (L+R)

CVBS

x1

YPbPr

x1

RS232

x 1

IR Pass Thru

x1

OUTPUT

DVI

x1

Audio

x1 Shared RCA audio (L+R)

RS232

x1

IR Pass Thru

x1

LAN

RJ45

x1

SPEAKERS

10Wx2

COMPATIBILITY

RGB PC/HDMI PC

Refer to timing table

CVBS

480i,

YPbPr

480i, 480p,720p,1080i,1080p

HDMI

480i, 480p,720p,1080i,1080p

DisplayPort

480i, 480p,720p,1080i,1080p

DVI

480i, 480p,720p,1080i,1080p

CONTROLS

Physical- Top OSD

PICTURE: POWER, MUTE, INPUT, VOL -/+, UP, DOWN, MENU

SCREEN: Brightness, Contrast, Sharpness,Black Level, Tint, Color, Color Temperature, Gamma Selection, Noise Reduction, Film Mode, Picture Reset

Auto Setup, Auto Adjust, H Position, V Position, Clock, Clock Phase, Zoom Mode, Custom Zoom, Input

Resolution, Screen Reset

SOUND: Balance, Treble, Bass, Audio Reset

PIP Mode, PIP Size, PIP Audio, PIP H Position, PIP V Position, SUB Input, PIP Reset

Off Timer, Schedule, Date and Time, CONFIGURATION 1 Reset

Language, OSD Turn Off, OSD H Position, OSD V Position, Information OSD, Monitor Information, Monitor ID, IR Control, Tiling, Power on Delay, Closed Caption, CONFIGURATION 2 Reset.

Power Save, Heat Status, Screen Saver, Side Border Color, CONFIGURATION 3 Reset

Input Change, Terminal Setting, Scan Conversion, Color System, Scan Mode, Serial Control, Lan Setting, APM, Advanced Option Reset, Factory Reset

POWER

Voltage

100-240VAC +/- 10% 50/60Hz Wide Range

Consumption

120W (typ), 150W (max)

< 0.5 W ("Off")

ERGONOMICS

Wall Mount (VESA®)

200 x 200 / 400 x 200

OPERATING CONDITIONS

Temperature (° C)

0°C to 40°C

Humidity

20% ~ 80% non-condensing

DIMENSIONS

(W x H x D)

Bezel width (B2B)

31.6 mm

Physical (inch / mm)

38.0x23.6x15.7 / 965.8x601.4x400 (w/ Stand)

38.0x22.0x2.7 / 965.8x558.8x69 (w/o Stand)

Packaging (inch / mm)

46.3x31.3x9.8 / 1178 x795x250

WEIGHT

Net (lb / kg)

40.26 / 18.3 (w/o Stand)

45.32 / 20.6 (w/ Stand)

Gross (lb / kg)

53.02 / 24.1

REGULATIONS

CE, CB, WEEE, C-tick, FCC, ICES003, UL/cUL, CE,CB, CU, Energy star 6.0

PACKAGE CONTENTS

1. CDP4260-L display 2. Remote Control with batteries 3. User manual CD wizard 4. Quick Start Guide 5. Power Cables 6. VGA cable

*Actual content may differ from market to market