
Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojektacji.pl



Nazwa

Monitor do ściany video Viewsonic Slim
Narrow Bezel for Seamless Video Wall
Installations CDP5560-L

Cena

0,00 zł

Producent

ViewSonic

OPIS PRODUKTU

LCD

Type

55" TFT LED Module with LED Backlight

Display Area

47.6" horizontal x 26.8" vertical; 55" diagonal

Optimum Resolution

1920 x 1080

Contrast Ratio

1300:1 (typ)

Viewing Angles

178° horizontal, 178° vertical

Response Time

12ms

Light Source

Long life, 50,000 hrs. (typ)

Brightness

450 cd/m2 (typ)

Aspect Ratio

16:9

Panel Surface

Hard coating (3H)

Dynamic Contrast Ratio

N/A
INPUT
PC
N/A
TV
N/A
Video Input
HDMI, DVI, DP, component (BNC), VGA
Video Output
VGA, DVI-D
Audio
N/A
Frequency
N/A
Sync
N/A
Digital
N/A
Tuner
N/A
Control Input Output
RS-232, RJ45
DISPLAY
Resolution
N/A
Touch
N/A
VIDEO SIGNAL
Video
480i, 480p, 720p, 1080i, 1080p
AUDIO
Speakers
Internal 10-watt (x2)
Amplifier
N/A
COMPATIBILITY
PC
N/A
Mac®
N/A
CONNECTOR
Analog
15-pin mini D-sub (VGA), RCA Audio In
Digital
HDMI, DVI-D, DisplayPort, YPbPr (BNC)
Power
3-pin plug
POWER
Voltage
AC 100–240V (universal), 50–60Hz
Consumption
245W (typ)
CONTROLS
Screen
Auto Setup, Auto Adjust, H Position, V Position, Clock, Clock Phase, Zoom Mode, Custom Zoom, Input

Resolution, Screen Reset

Input

N/A

Basic

N/A

Picture

Brightness, Contrast, Sharpness, Black Level, Tint, Color, Color Temperature, Gamma Selection, Noise Reduction, Film Mode, Picture Reset

Audio

N/A

Sound

Balance, Treble, Bass, Audio Reset

OSD

N/A

Panel

POWER, MUTE, INPUT, VOL +/-, UP, DOWN, MENU

VGA Setting

N/A

Special

PIP Mode, PIP Size, PIP Audio, PIP H Position, PIP V Position, SUB input, PIP Reset

Diagnostic

N/A

Set Up

Off Timer, Schedule, Data and Time, Configuration 1 Reset Configuration 2 Language, OSD Turn Off, OSD H Position, OSD V Position, Information OSD, Monitor Information, Monitor ID, IR Control, Tiling, Power on Delay, Closed Caption, Reset Power Save, Heat Status, Screen Saver, Side Border Color, Reset

TV

N/A

Advanced Options

Input Change, Terminal Setting, Scan Conversion, Color System, Scan Mode, Serial Control, LAN Setting, APM, Advanced Option Reset, Factory Reset

OPERATING CONDITIONS

Humidity

20–80% (non-condensing)

Temperature(landscape)

32–104°F (0–40°C)

Temperature(Portrait)

N/A

DIMENSIONS (WxHxD)

Physical Without Stand

49.1 x 28.3 x 2.8 in. / 1247 x 717.8 x 70 mm

WEIGHT

Gross

79.5 lb. / 36.1 kg

Net Without Stand

67.4 lb. / 30.6 kg

Net With Stand

N/A

Regulations

CE, CB, WEEE, C-tick, FCC, ICES003, UL/cUL, CE, CB, CU, ENERGY STAR 6.0

Wall Mount

400mm x 400mm

Recycle/Disposal

Please dispose of in accordance with local, state or federal laws.

PACKAGE CONTENTS

CDP5560-L display, power cable, VGA cable, remote control with batteries, Quick Start Guide,

ViewSonic Wizard CD (with User Guide)

Optional Accessories (sold separately)

Stand (STND-021)

Wall Mount Kit (WMK-014)

Warranty

Three-year limited warranty on parts, labor and backlight