

---

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl

---



Nazwa

Monitor do ściany video Viewsonic Slim  
Narrow Bezel for Seamless Video Wall  
Installations CDP5562-L

Cena

**0,00 zł**

Producent

**ViewSonic**

---

## OPIS PRODUKTU

LCD

Type

55" TFT LED Module with LED Backlight

Display Area

47.6" horizontal x 26.8" vertical; 55" diagonal

Optimum Resolution

1920 x 1080 HD

Contrast Ratio

1300:1 (typ)

Viewing Angles

178° horizontal, 178° vertical

Response Time

12ms

Light Source

Long life, 50,000\* hrs. (typ)

Brightness

700 cd/m2 (typ)

Aspect Ratio

16:9

Panel Surface

Hard coating (3H)

INPUT

## Video Input

HDMI, DVI, DP, component (BNC), VGA

## Video Output

VGA, DVI-D

## Control Input Output

RS232, RJ45

## DISPLAY

### Resolution

1920 x 1080

### Touch

N/A

## VIDEO SIGNAL

### Video

480i, 480p, 720p, 1080i, 1080p

## AUDIO

### Speakers

Internal 10-watt (x2)

## CONNECTOR

### Analog

15-pin mini D-sub (VGA), RCA Audio In

### Digital

HDMI, DVI-D, DisplayPort, YPbPr (BNC)

### Power

3-pin plug

## POWER

### Voltage

AC 100–240V (universal), 50–60Hz

### Consumption

245W (typ)

## CONTROLS

### Screen

Auto Setup, Auto Adjust, H Position, V Position, Clock, Clock Phase, Zoom Mode, Custom Zoom, Input Resolution, Screen Reset

### Picture

Brightness, Contrast, Sharpness, Black Level, Tint, Color, Color Temperature, Gamma Selection, Noise Reduction, Film Mode, Picture Reset

### Sound

Balance, Treble, Bass, Audio Reset

### Panel

POWER, MUTE, INPUT, VOL +/-, UP, DOWN, MENU

### Special

PIP Mode, PIP Size, PIP Audio, PIP H Position, PIP V Position, SUB input, PIP Reset

### Set Up

Configuration 1: Off Timer, Schedule, Date and Time, Configuration 1 Reset

Configuration 2: Language, OSD Turn Off, OSD H Position, OSD V Position, Information OSD, Monitor Information, Monitor ID, IR Control, Tiling, Power on Delay, Closed Caption, Configuration 2 Reset

Configuration 3: Power Save, Heat Status, Screen Saver, Side Border Color, Configuration 3 Reset

### Advanced Options

Input Change, Terminal Setting, Scan Conversion, Color System, Scan Mode, Serial Control, LAN Setting, APM, Advanced Option Reset, Factory Reset

## OPERATING CONDITIONS

### Humidity

20–80% (non-condensing)

### Temperature(landscape)

32–104°F (0–40°C)

DIMENSIONS (WxHxD)

Physical Without Stand

49.1 x 28.3 x 2.8 in. / 1247 x 717.8 x 70 mm

WEIGHT

Gross

79.5 lb. / 36.1 kg

Net Without Stand

67.4 lb. / 30.6 kg

Regulations

CE, CB, WEEE, C-tick, FCC, ICES003, UL/cUL, CE, CB, CU, ENERGY STAR 6.0

Wall Mount

VESA® 400mm x 400mm

Recycle/Disposal

Please dispose of in accordance with local, state or federal laws.

PACKAGE CONTENTS

CDP5562-L display, power cable, VGA cable, remote control with batteries, Quick Start Guide, ViewSonic Wizard CD (with User Guide)

Optional Accessories (sold separately)

Stand (STND-021), Wall Mount Kit (WMK-014)

Warranty

Three-year limited warranty on parts, labor and backlight