
Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Nazwa

Monitor do ściany video Viewsonic Slim
Narrow Bezel for Seamless Video Wall
Installations CDX4652-L

Cena

0,00 zł

Producent

ViewSonic

OPIS PRODUKTU

LCD

Type

46" TFT LED Module with LED Backlight

Display Area

40.1" horizontal x 22.5" vertical; 46" diagonal

Optimum Resolution

1920 x 1080

Contrast Ratio

3500:1 (typ)

Viewing Angles

178 horizontal, 178 vertical

Response Time

8ms

Light Source

Long life, 50,000* hrs. (typ)

Brightness

500 cd/m2 (typ)

Aspect Ratio

16:9

Panel Surface

Anti-glare, Hard coating (3H)

INPUT

Video Input

HDMI, DVI, DP, component (BNC), VGA

Video Output

VGA, DVI-D

Control Input Output

RS232, RJ45

DISPLAY

Resolution

1920 x 1080

Touch

N/A

VIDEO SIGNAL

Video

TV/Video Comp. 480i, 480p, 720p, 1080i, 1080p

AUDIO

Speakers

Internal 10-watt (x2)

CONNECTOR

Analog

15-pin mini D-sub (VGA), RCA Audio In

Digital

HDMI, DVI-D, DisplayPort, YPbPr (BNC)

Power

3-pin plug

POWER

Voltage

AC 100–240V (universal), 50–60Hz

Consumption

120W (typ)

CONTROLS

Screen

Auto Setup, Auto Adjust, H Position, V Position, Clock, Clock Phase, Zoom Mode, Custom Zoom, Input Resolution, Screen Reset

Picture

Brightness, Contrast, Sharpness, Black Level, Tint, Color, Color Temperature, Gamma Selection, Noise Reduction, Film Mode, Picture Reset

Sound

Balance, Treble, Bass, Audio Reset

Panel

POWER, MUTE, INPUT, VOL +/-, UP, DOWN, MENU

Special

PIP Mode, PIP Size, PIP Audio, PIP H Position, PIP V Position, SUB input, PIP Reset

Set Up

Configuration 1: Off Timer, Schedule, Date and Time, Configuration 1 Reset

Configuration 2: Language, OSD Turn Off, OSD H Position, OSD V Position, Information OSD, Monitor Information, Monitor ID, IR Control, Tiling, Power on Delay, Closed Caption, Configuration 2 Reset

Configuration 3: Power Save, Heat Status, Screen Saver, Side Border Color, Configuration 3 Reset

Advanced Options

Input Change, Terminal Setting, Scan Conversion, Color System, Scan Mode, Serial Control, LAN Setting, APM, Advanced Option Reset, Factory Reset

OPERATING CONDITIONS

Humidity

20–80% (non-condensing)

Temperature(landscape)

32–104° F (0–40° C)

DIMENSIONS (WxHxD)

Physical Without Stand

40.3 x 22.8 x 4.9 in. / 1024 x 578.6 x 125.7 mm

WEIGHT

Gross

70.3 lb. / 31.9 kg

Net Without Stand

50.7 lb. / 23 kg

Regulations

CE, CB, WEEE, C-tick, FCC, ICES003, UL/cUL, CE, CB, CU, ENERGY STAR 6.0

Wall Mount

VESA 400 x 200 mm / 200 x 200 mm

Recycle/Disposal

Please dispose of in accordance with local, state or federal laws.

PACKAGE CONTENTS

CDX4652-L display, power cable, VGA cable, remote control with batteries, Quick Start Guide, ViewSonic Wizard CD (with User Guide)

Optional Accessories (sold separately)

Stand (STND-021), Wall Mount Kit (WMK-013)

Warranty

Three-year limited warranty on parts, labor and backlight

Notices

*Lifespan may vary based on actual usage and other factors. Warranty exclusions may apply.