

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



ViewSonic
See the difference™

Nazwa

**Monitor Dotykowy 4K ViewSonic
ViewBoard 7552-1C**

Cena

0,00 zł

Producent

ViewSonic

OPIS PRODUKTU

Display

Panel Size: 75"

Panel Type: TFT LCD Module with DLED Backlight.

Display Area (mm): 1649.644(H) x 927.936(V)

Aspect Ratio: 16:9

Resolution: UHD 3840x2160(Pixels)

Colors: 1.07B colors (10bit)

Brightness: 400 nits (typ)

Contrast Ratio: 1200:1 Typ. , 4000:1 Max.(DCR enable)

Response Time: 8ms

Viewing Angles: H = 178, V = 178 typ.

Backlight Life: 50,000 hrs (typ)

Surface Treatment: Hardness: 9H. Anti-glare coating

Orientation: Landscape

Platform

Processor: ARM Cortex A73*4

RAM: 4GB

Storage: 32 GB

Touch

Type/ Tech: UFT (Ultra Fine Touch) Technology

Touch Resolution: 32767 x 32767

Touch Point: Windows: 33 points touch, Android: 20 points touch

INPUT

HDMI: 2.0 x4 (3840x2160 @60Hz ,HDCP2.2, HDMI2 with CEC/ARC)

RGB / VGA: x1 (1920x1080 @60Hz)

Audio: x1 (PC audio in)

RS232: x1

OPS: module slot x 1

WiFi: WiFi module slot x 1

OUTPUT

HDMI: x1(3840x2160@60Hz)

Audio: x1 (Earphone out)

SPDIF: x1 (optical)

LAN

RJ45: x1

USB

Type A: USB2.0 x 3 (Front x2, Side x1)

USB3.0 x 2 (Side x 2)

Type B: x3(Front x1, Rear x 2)), for touch

Type C: x1 (USB2.0, DP1.2, Ethernet, PD 65W)

SPEAKERS

15W x 2 front soundbar + 15W x 1 subwoofer

MICROPHONE

built-in 8-array microphone

Top Camera Plate

Yes

Embedded OS

9.0

Bundle Software

Basic Annotation Software: myViewBoard WhiteBoard for Android

Pro Annotation Software: myViewBoard WhiteBoard for Windows (embedded in VPC)

Wireless Presentation: ViewBoard Cast & myViewBoard Display

Special Features

All-in-one USB port: USB 3.0 x 2

Simple LAN sharing between IFP and slot-in device: 10/100/1000M for Android and PC

Light Sensor: Yes

Power

Voltage: 100-240VAC +/- 10% Wide Range

Consumption: 129.5W(typ.) / Off: <0.5W

ERGONOMICS

Wall Mount (VESA®): 800 x 400

OPERATING CONDITIONS

Temperature (° C): 0°C to 40°C

Humidity: 10% ~ 90% RH Non-Condensing

DIMENSIONS (W x H x D)

Physical (inch / mm): 1709 x 1071 x 120 mm / 67.3 x 42.2 x 4.7 in

Packaging (inch / mm): 1848 x 1190 x 270 mm /72.7 x 46.8 x 10.6 in

WEIGHT

Net (lb / kg): 121.81lb/55.25kg

Gross (lb / kg): 170.81lb/77.48kg

REGULATIONS

cTUVus, FCC/ICES003, Energy star 8.0, Mexico CoC, Mexico Energy, EMC/CE, CB/LVD, EAC, UkrSEPRO,

LBL, FF, Green BOM, RoHS, SCIP, WEEE , EPEAT, BSMI, ErP, REACH , TPCH, CA65, PAIA

PACKAGE CONTENTS

1.Power cable 2. Remote control 3. USB Type-C cable 4. USB Touch cable 5. Touch pen x 2 6. Quick Start Guide + Compliance statement 7. RS232 adapter 8. Clamp x 5 9. Camera Plate 10. Screw x 8 11. HDMI cable 12. Eraser 13. AAA Battery x 2

Compatible Slot-in PC

VPC12 & VPC25/27-O & VPC25/27-O-B series