

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



ViewSonic
See the difference™

Nazwa

**Monitor Dotykowy 4K ViewSonic
ViewBoard 8652-1C**

Cena

0,00 zł

Producent

ViewSonic

OPIS PRODUKTU

Display

Panel Size: 86"

Panel Type: TFT LCD Module with DLED Backlight

Display Area (mm): 1895.04(H) x 1065.96(V)

Aspect Ratio: 16:9

Resolution: UHD 3840x2160(Pixels)

Colors: 1.07B colors (10bit)

Brightness: 400 nits (typ)

Contrast Ratio: 1100:1 Typ. , 2500:1 Max.(DCR enable)

Response Time: 8ms

Viewing Angles: H = 178, V = 178 typ.

Backlight Life: 50,000 hrs (typ)

Surface Treatment: Hardness: 9H. Anti-glare coating

Orientation: Landscape

Platform

Processor: ARM Cortex A73*4

RAM: 4GB DDR4

Storage: 32GB

Touch

Type/ Tech: UFT (Ultra Fine Touch) Technology

Touch Resolution: 32767 x 32767

Touch Point: Windows: 33 points touch, Android: 20 points touch

INPUT

HDMI: 2.0 x4 (3840x2160 @60Hz ,HDCP2.2, HDMI2 with CEC/ARC)

RGB / VGA: x1 (1920x1080 @60Hz)

Audio: x1 (PC audio in)

RS232: x1

OPS: module slot x 1

WiFi: WiFi module slot x 1

OUTPUT

HDMI: x1 (3840x2160 @60HZ)

Audio: x1 (Earphone out)

SPDIF: x1 (optical)

LAN

RJ45: x1

USB

Type A: USB2.0 x 3 (Front x2, Side x1)

USB3.0 x 2 (Side x 2)

Type B: x3(Front x1, Rear x 2)), for touch

Type C: x1 (USB2.0, DP1.2, Ethernet, PD 65W)

SPEAKERS

15W x 2 front soundbar + 15W x 1 subwoofer

MICROPHONE

built-in 8-array microphone

Top Camera Plate

YES

Embedded OS

Android 9

Bundle Software

Basic Annotation Software: myViewBoard WhiteBoard for Android

Pro Annotation Software: myViewBoard WhiteBoard for Windows (embedded in VPC)

Wireless Presentation: ViewBoard Cast & myViewBoard Display

Special Features

All-in-one USB port: USB 3.0 x 2

Simple LAN sharing between IFP and slot-in device: 10/100/1000M for Android and PC

Light Sensor: Yes

Power

Voltage: 100-240VAC +/- 10% Wide Range

Consumption: 150.4 W (typ.) / Off: <0.5W

ERGONOMICS

Wall Mount (VESA®): 800 x 600

OPERATING CONDITIONS

Temperature (° C): 0°C to 40°C

Humidity: 10% ~ 90% RH non-condensing

DIMENSIONS (W x H x D)

Physical (inch / mm): 1957 x 1211 x 120 mm / 77 x 47.7 x 4.7 in

Packaging (inch / mm): 2102 x 1330 x 270 mm /82.7 x 52.3 x 10.6 in

WEIGHT

Net (lb / kg): 151.35lb/68.65kg

Gross (lb / kg): 179.46lb/81.40kg

REGULATIONS

cTUVus, FCC/ICES003, Energy star 8.0, Mexico CoC, Mexico Energy, EMC/CE, CB/LVD, EAC, UkrSEPRO,

LBL, FF, Green BOM, RoHS, SCIP, WEEE , EPEAT, BSMI, ErP, REACH , TPCH, CA65, PAIA

PACKAGE CONTENTS

1. Power cable (3 meters) 2. Remote control 3. USB Type-C cable (1.5 meters) 4. USB Touch cable (3 meters, USB2.0) 5. Touch pen x 2 6. Quick Start Guide + Compliance statement 7. RS232 adapter 8.

Clamp x 5 9. Camera Plate 10. Screw x 8 (camera 2+2, wall mount 4) 11. HDMI cable (3 meters) 12.

Eraser 13. AAA Battery x 2

Compatible Slot-in PC

VPC12 & VPC25/27-O & VPC25/27-O-B series

Note

Disclaimer:

1.Although we endeavor to present the most accurate and comprehensive information at the time of

publication, we reserve the right to make any change regarding any info herein without prior notice.

2. Unless otherwise stated, all performance claims are based on theoretical performance. Actual figures may vary in real-world situations and may depend on many factors including the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment.

3. Product Specification and appearance may differ from country to country and from model to model. We recommend that you check with your local dealers for the specification and the appearance of the product model available in your country. Colors of products may not be perfectly accurate due to variations caused by photography and monitor settings.