

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



**ViewSonic**  
See the difference™ 

Nazwa

**Monitor Dotykowy 4K ViewSonic  
ViewBoard IFP7552-1BH**

Cena

**0,00 zł**

Producent

**ViewSonic**

## OPIS PRODUKTU

### Display

Panel Size: 75"

Panel Type: TFT LCD Module with DLED Backlight

Display Area (mm): 1649.644(H) x 927.936(V)

Aspect Ratio: 16:9

Resolution: UHD 3840x2160(Pixels)

Colors: 1.07B colors (10bit)

Brightness: 400 nits (typ.)

Contrast Ratio: 1200:1 Typ. , 5000:1 Max.(DCR enable)

Response Time: 8ms

Viewing Angles: H = 178, V = 178 typ.

Backlight Life: 50,000 Hours (Typ.)

Surface Treatment: Hardness: 9H with Anti-Fingerprint coating & Anti-Glare coating

### Platform

Processor: ARM Cortex A73\*4

RAM: 8GB

Storage: 64GB

### Touch

Type/ Tech: UFT (Ultra Fine Touch) Technology

Touch Resolution: 32767 x 32767

Touch Point: Windows: 33 points touch, Android: 20 points touch

### INPUT

HDMI: x2 (3840x2160@60Hz, HDCP2.2, CEC, Front x1, Side x1), x1 (3840x2160@60Hz, HDCP2.2, CEC, ARC, Side x 1)

RGB / VGA: x1 (1920x1080 @60Hz)

DisplayPort: x1 (3840x2160 @60Hz)

Audio: x1 (PC audio in)

RS232: x1

OPS: module slot x 1

WiFi: module slot x 1

OUTPUT

HDMI: x1 (on demand)

Audio: x1 (Earphone out)

SPDIF: x1 (optical)

LAN

RJ45: x1

USB

Type A: USB 2.0 x1(Side x1), USB 3.0 x4 (Front x2, Side x2, SmartPort™ USB)

Type B: x2, for touch

Type C: x1 (USB3.0, DP1.2 Alt Mode, 100M Ethernet, 60W PD)

SPEAKERS

20W x 2 + 40W x 1 subwoofer

MICROPHONE

built-in 8-array microphone

Top Camera Plate

Yes

Embedded OS

Android 9

Bundle Software

Basic Annotation Software: myViewBoard WhiteBoard for Android

Pro Annotation Software: myViewBoard WhiteBoard for Windows (embedded in VPC)

Wireless Presentation: ViewBoard Cast & myViewBoard Display

Special Features

All-in-one USB port: USB 3.0 x 4

Simple LAN sharing between IFP and slot-in device: 10/100/1000M for Android and PC

Light Sensor: Yes

Power

Voltage: 100-240VAC +/- 10% Wide Range

Consumption: On: 149.97W(typ.) / Off: <0.5W

ERGONOMICS

Wall Mount (VESA® ): 800 x 400

OPERATING CONDITIONS

Temperature (° C): 0°C to 40°C

Humidity: 20% ~ 80% RH Non-Condensing

DIMENSIONS (W x H x D)

Physical (inch / mm): 1720.1 (W) x 1069.6 (H) x 118.4 (D) mm, 67.72 (W) x 42.11 (H) x 4.66 (D) inch

Packaging (inch / mm): 1880 (W) x 1160 (H) x 280 (D) mm, 74.02 (W) x 45.67 (H) x 11.02 (D) inch

WEIGHT

Net (lb / kg): 125.22 lb / 56.8 kg

Gross (lb / kg): 158.95 lb / 72.1 kg

REGULATIONS

EMC/CE, CB, RoHS & DOC, REACH, WEEE, ErP. EEI

PACKAGE CONTENTS

1. Power cable(3 meters) 2. Remote control 3. USB Type-C cable (1.5 meters) 4. USB Touch cable (3 meters, USB2.0) 5. Touch pen x 2 6. Quick Start Guide + Compliance statement 7. RS232 adapter 8. Clamp x 5 9. Camera Plate 10. Screw x 8 (camera 2+2, wall mount 4) 11. HDMI cable (3 meters) 12. Eraser 13. AAA Battery x 2

Compatible Slot-in PC  
VPC12-WPO/VPC2C-O/VPC25-O/VPC27-O series