

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Nazwa **Monitor dotykowy Viewsonic 65"  
Interactive Large Format Display CDE6560T**

Cena **0,00 zł**

Producent **ViewSonic**

## OPIS PRODUKTU

### SPECIFICATIONS

#### LCD PANEL

Panel Size : 65" (64.5" viewable)

Type/ Tech : TFT LCD Module with LED Backlight

Display Area (mm) : 1428.48(H) x 803.52(V) (64.5" diagonal)

Aspect Ratio : 16:9

Resolution : 1920x1080

Colors : 10 bit, 1.07B colors

Brightness : 360 nits (typ.)

Contrast Ratio : 4000:1 Typ.

Response Time : 8ms

Viewing Angles : H = 178, V = 178

Backlight : LED

Backlight Life : 50,000 Hours Typ

Hardness : 7H

#### TOUCH

Type/ Tech : Infrared

Touch Resolution : 32767 x 32767

Touch Point : 10 point for gesture, 5 point for writing

Response Time : 15ms MAX.

System : Windows8/Windows7/WindowsXP/Vista/Linux/Mac/Android/Wince/Chrome

#### INPUT

HDMI : x3  
RGB / VGA : x3  
DisplayPort : N/A  
DVI : N/A  
RF (TV) : N/A  
Audio : x3 (PC audio in)  
CVBS : x1  
YPbPr : N/A  
MIC(Microphone) : N/A  
RS232 : x1  
SD/SDHC : N/A  
OPS / ViewSonic PC Module Slot : N/A / x1 (for NMP710)

#### OUTPUT

RGB / VGA : x1  
DisplayPort : N/A  
DVI : N/A  
Audio : x1 (Earphone out)  
CVBS : N/A  
YPbPr : N/A  
SPIDF : x1 (optical)  
RS232 : N/A  
Remote Control : N/A  
LAN  
RJ45 : x1  
USB

Type A : x3 (2.0); x1 (3.0)

Type B : x1 (for touch)

Mini USB : N/A

Micro USB : N/A

#### SPEAKERS

10W x 2

#### BUILT-IN PC

Processor : ARM Cortex A9 Dual Core CPU

Graphic : ARM Mali400 MP4

Sound Card : N/A

Memory : 1.5GB

Storage : 8GB

Networking : Integrated 10/100/1000M Adaption

#### COMPATIBILITY

RGB PC/HDMI PC : Refer to timing table

CVBS : 480i

S-Video : N/A

YPbPr : N/A

HDMI : 480i, 480p,720p, up to 1080

#### CONTROLS

Physical- Top OSD : Power, Home, Return, Setting, VOL-, VOL+ INPUT: PC, Android, AV, VGA1, VGA2, VGA3, HDMI1, HDMI2, HDMI3, HDMI4 LIGHT: 1~10 VOLUME: 0~100 VGA: H Position, V Position, Phase, Clock, Zoom, Auto Adjust, Writing Mode PICTURE: Brightness, Contrast, Hue, Sharpness, Color Temp, Zoom, Writing Mode

Embedded Linux OS : SETTING: Ethernet checking, Sound, Display, Apps, Language&input, Date&time, About device ANNOTATION: Annotation menu, Return, Main, Pen, ViewBoard Lit, Open file, Screenshot, close menu INTERFACE: ViewBoard Lit, Folders, Browser, PIP, Settings, Apps

Multimedia : IMAGE: Close, Zoom in, Zoom out, Previous, Play/Pause, Next, Counterclockwise, Clockwise, setting AUDIO: Close, Previous, Play/Pause, Next, Playlist, Loop, Random, Single VIDEO: Close, Previous, Fast backward, Play/Pause, Fast forward, Next, Playlist

## POWER

Voltage : 100-240VAC +/- 10% Wide Range

Consumption : "On" 270W(typ), "Power Saving" < 0.5 W, "Off" (Suspend) < 0.5 W

## ERGONOMICS

Tilt : N/A

Wall Mount (VESA®) : 600 x 400 (M8 x 60mm) With Wall Mount Spacer

## OPERATING CONDITIONS

Temperature (° C) : 32°F to 104°F (0°C to 40°C)

Humidity : 20% ~ 80% non-condensing

## DIMENSIONS (W X H X D)

Physical (inch / Mm) : 60.8x36.9x3.8 / 1545x937x96

Packaging (inch / Mm) : 67.5x42.7x11.0 / 1715x1085x280

## WEIGHT

Net (lb / Kg) : 152.12 / 69

Gross (lb / Kg) : 176.37 / 80

## WARRANTY

\*\*Warranty offered may differ from market to market

## WHAT'S IN THE BOX?

- CDE Interactive Large Format Display Monitor
- VGA cable
- Power cable x 4
- Remote control
- USB cable
- Audio cable
- Touching pen x 3
- User manual CD wizard
- RS232 adapter
- Wall Mount Spacer
- Wall Mount Kit: WMK-047 (in separate box, for Europe only)