

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Nazwa

**Monitor dotykowy Viewsonic 84" LCD  
6-Point Multi-Touch Display SWB8451**

Cena

**0,00 zł**

Producent

**ViewSonic**

## OPIS PRODUKTU

### SPECIFICATIONS

#### REMOTE CONTROL UNIT (RCN)

Type : IR

#### LCD

Effective Viewing Area : 3,840 (H) x 2,160 (W) (84.04" diagonal)

Contrast Ratio : 1600:1 (typ.)

Viewing Angles : H = 89, V = 89 (typ.)

Brightness : CR : 5,000 (typ.) / 350 nits (typ.)

Response Time : Total (ON + OFF) = 8ms

Native Resolution : 1920 x 1080p @60Hz

Panel Surface : Anti-glare

Colour Support : 1.06B colors

Size : 84"

### DIMENSIONS

Physical (WxHxD) : 1,978 x 1,186 x 86 mm / 77.9 x 46.7 x 3.4 in

### WEIGHT

Wall Mount : 6.5 kgs / 14.33 lbs

### DIMENSIONS

Display : 2,180 x 1,480 x 340 mm / 85.83 x 58.27 x 13.39 in

### POWER

Voltage : 100-240VAC +/- 10% Wide Range

### CONTROLS

OSD : \*1

Physical : Top: POWER, INPUT, MENU, CH ^, CH v, VOL+, VOL-

VESA® MOUNT

600 x 600mm

## INCLUDED ACCESSORIES

1. VGA cable
2. Power cable x 4
3. Remote control
4. USB cable
5. Audio cable
6. Touching pen x 3
7. User manual CD wizard

## AUDIO

Speakers : 15W x 2 @THD = 10%

Microphone : None

## WEIGHT

Gross : 140 kgs / 308.65 lbs

Net : 116 kgs / 255.74 lbs

## STORAGE / SHIPPING CONDITION

Humidity : 10% ~ 90%, non-condensing

Temperature : -4°F to 140°F (-20°C to 60°C)

Altitude : N/A

## RELIABILITY

Backlight : 30,000 Hours (typ.)

## BUILT-IN PC

Processor : Intel Core i3 (SWB8451-3\_ SWB8451-3) Intel Core i5 (SWB8451-5\_ SWB8451-5)

Graphics : Integrated Intel HD 3000

Sound Card : Integrated High Definition Audio Stereo

Memory : DDR III 2GB (SWB8451-3\_ SWB8451-3) DDR III 4GB (SWB8451-5\_ SWB8451-5)

Storage : 2.5" SATA2 HDD 320GB (SWB8451-3\_ SWB8451-3) 2.5" SATA2 HDD 500GB (SWB8451-5\_ SWB8451-5)

Networking : Integrated 10/100/1000M Adaption

## REMOTE CONTROL UNIT (RCN)

Range : Straight-line distance: 8M

Transmit angle  $\pm 30^\circ$  3 6M

## INPUT / OUTPUT

Connector : Display: HDMI x 2 RGB x 2 PC audio (mini stereo) x 2 S-Video x 1 CVBS IN x 1 CVBS OUT x 1

Shared RCA Audio x 1 YPbPr x1 USB A Type (for F/W) x 1 USB B Type (for touch) x 1 SPIDF x 1 RS232 x 1

PC: AUDIO OUT x 1 MIC x 1 VGA OUT x 1 LAN IN x 1 USB x 4

## VIDEO FORMAT

Compatibility : RGB PC/HDMI PC: Refer to timing table

CVBS: 480i

S-Video: 480i, 576i

YPbPr: 480i, 480p, 720p, up to 1080p

HDMI: 480i, 720p, up to 1080p

## POWER SAVING FUNCTION

On : Green indicator, < TBDW

Power-saving Mode : Green indicator flashing, < 0.5 W

Off (Suspend) : Red indicator, < 0.5 W

## DISPLAY PC/RGB MODES

Supported : Refer to the compatibility table

\*If a mode isn't specifically listed, full compatibility is not guaranteed. Results may vary between video cards / drivers.