

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



ViewSonic
See the difference™

Nazwa

Monitor dotykowy Viewsonic flat panel display with touchscreen SWB7051

Cena

0,00 zł

Producent

ViewSonic

OPIS PRODUKTU

SPECIFICATIONS

LCD

Type : TFT LCD Module with LED Backlight

Effective Viewing Area : 1538.88 (H) x 865.62 (V) (69.5" Diagonal)

Contrast Ratio : 4000:1 Typ.

Viewing Angles : 88° Horizontal, 88° Vertical

Response Time : 6ms

Aspect Ratio : 16:9

Native Resolution : 1920 x 1080

S-Video-In : 480i, 576i

Size : 69.5"

Backlight : LED

Backlight Life : 50,000 Hours Typ.

COMPATIBILITY

RGB PC / HDMI PC : Refer to timing table

CONNECTOR

CVBS : x1

COMPATIBILITY

HDMI : 480i, 480p, 720p, up to 1080p

YPbPr : 480i, 480p, 720p, up to 1080p

DIMENSIONS

Physical (WxHxD) : 64.9 x 39.3 x 3.8 (inches) / 1649 x 999 x 97 (mm)

Packaging : 70.3 x 44.9 x 10.8 (inches) / 1785x1140x275 (mm)

AUDIO

RCA : x1

Speakers : 15W x2

CONNECTOR

Audio Out : x1

HDMI (input) : x2

RS-232 : x1

RGB : x2

USB : x6

Audio : Mini-stereo x2

PC-VGA-Out : x1

LAN : x1

Mic In/Out : x1

POWER

Voltage : 100-240VAC +/- 10% Wide Range

CONTROLS

Picture : Picture Mode, Contrast, Brightness, Color, Tint, Sharpness, Color Temp., Noise Reduction

Set Up : OSD Language, TT Language, Hearing Impaired, PVR File System, Record List, Aspect Ratio, Blue Screen, First Time Installation, Reset, Software Update (USB)

Configuration 1 : Time: Clock, Time Zone, Sleep Timer, Auto Standby, OSD Timer

Configuration 2 : Lock: Lock System, Set Password, Block Program, Parental Guidance, Key Lock

Physical : POWER, INPUT, PC/VGA, VOL+, VOL-, ZOOM, ENERGY SAVING

Sound : Sound Mode, Treble, Bass, Balance, Auto Volume, SPDIF MODE, AD Switch

VESA® MOUNT

600 x 600

INCLUDED ACCESSORIES

VGA Cable x1

Power Cable x4

Remote Control x1

USB Cable x1

Audio Cable x1

Stylus x3

User Manual CD Wizard x1

WEIGHT

Gross : 187.4 (lb) / 85 (kg)

Net : 165.3 (lb) / 75 (kg)

OPERATING CONDITIONS

Humidity : 20% ~ 80% Non-condensing

Temperature : 32°F to 104°F (0°C to 40°C)

WARRANTY

**Warranty offered may differ from market to market

VIDEO I/O

YPbPr In : x1

AUDIO I/O

SPDIF Out : x1

INPUT

USB Type A : x1

USB Type B (mouse Control) : x2

BUILT-IN PC

Processor : Intel Core i5

Graphics : Integrated Intel HD 3000

Sound Card : Integrated High Definition Audio Stereo

Memory : DDR III 4GB

Storage : 2.5" SATA2 HDD 500GB

Networking : Integrated 10/100/1000M Adaption