

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



ViewSonic
See the difference™ 

Nazwa **Monitor Dotykowy ViewSonic TD2760**

Cena **0,00 zł**

Producent **ViewSonic**

OPIS PRODUKTU

Specyfikacja techniczna:

DISPLAY

Display Size (in.): 27

Viewable Area (in.): 27

Panel Type: VA Technology

Resolution: 1920 x 1080

Resolution Type: FHD

Static Contrast Ratio: 3,000:1 (typ)

Dynamic Contrast Ratio: 50M:1

Light Source: LED

Brightness: 230 cd/m2 with touch; 300 cd/m2 without touch

Colours: 16.7M

Colour Space Support: 8 bit (6 bit + Hi-FRC)

Aspect Ratio: 16:9

Response Time (Typical GTG): 6ms

Response Time (GTG w/OD): 6ms

Viewing Angles: 178° horizontal, 178° vertical

Backlight Life (Hours): 30000 Hrs (Min)

Curvature: Flat

Refresh Rate (Hz): 60

Blue Light Filter: Yes

Flicker-Free: Yes

Colour Gamut: NTSC: 72% size (Typ)

Pixel Size: 0.311 mm (H) x 0.311 mm (V)

COMPATIBILITY

PC Resolution (max): 1920x1080

Mac® Resolution (max): 1920x1080

PC Operating System: Windows 7/8.1/10 certified; macOS tested

Mac® Resolution (min): 1920x1080

CONNECTOR

VGA: 1

USB 3.0 Type A: 2

USB 3.0 Type B: 1

3.5mm Audio In: 1

3.5mm Audio Out: 1

Display Port: 1

Power in: 3-pin Socket (IEC C14 / CEE22)

RS232 In: 1

TOUCH

Touch Technology: Capacitive multi-point touch

Touch Points: 10

Surface Treatment: Anti-Glare, Hard Coating (□6H)

Glass Thickness: 1.88mm

AUDIO

Internal Speakers: 2Watts x2

POWER

Eco Mode (Conserve): 19W

Eco Mode (optimized): 22W

Consumption (typical): 26W

Consumption (max): 28W

Voltage: AC 100-240V, 50/60 Hz

Stand-by: 0.3W

Power Supply: Internal

ADDITIONAL HARDWARE

Kensington Lock Slot: 1

CONTROLS

Physical Controls: 1, 2, Up, Down, Power

On Screen Display: Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Setup Menu, Memory Recall

OPERATING CONDITIONS

Temperature: 32°F to 104°F (0°C to 40°C)

Humidity (non-condensing): 20% to 90%

WALL MOUNT

VESA Compatible: 100 x 100 mm

INPUT SIGNAL

Frequency Horizontal: 15 ~ 90KHz

Frequency Vertical: 50 ~ 76Hz

VIDEO INPUT

Digital Sync: TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2)

Analog Sync: Separate/Composite/SOG - RGB Analog

ERGONOMICS

Tilt (Forward/Back): -4° / 90°

WEIGHT (IMPERIAL)

Net (lbs): 17.4

Net Without Stand (lbs): 12.2

Gross (lbs): 22.6

WEIGHT (METRIC)

Net (kg): 7.9

Net Without Stand (kg): 5.5

Gross (kg): 10.2

DIMENSIONS (IMPERIAL) (WXHxD)

Packaging (in.): 29.6 x 20.7 x 8

Physical (in.): 26 x 17.5 x 9.4

Physical Without Stand (in.): 26 x 16.2 x 2.3

DIMENSIONS (METRIC) (WXHxD)

Packaging (mm): 753 x 525 x 204

Physical (mm): 660 x 443 x 239

Physical Without Stand (mm): 660 x 410 x 58

GENERAL

Regulations: cTUVus, FCC-B, ICES003, Energy Star 8.0, EPEAT Bronze, CEC, MX-CoC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, RCM, GEMS

PACKAGE CONTENTS: TD2760 x1, 3-pin Plug (IEC C13 / CEE22) x1, VGA Cable (Male-Male) x1, HDMI Cable (v1.4; Male-Male) x1, Audio Cable (Male-Male) x1, USB A/B Cable (v3.0; Male-Male) x1, Quick Start Guide x1

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

Warranty: *Warranty offered may differ from market to market

Country Of Origin: China

Power Management: Energy Star standards

Internal Speakers

VESA Compatible(Wall Mount 100x100mm)

AC In

DisplayPort

HDMI

VGA

USB Down Stream X 2

USB Up Stream

RS232