

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



**ViewSonic**  
See the difference™ 

Nazwa

**Monitor Dotykowy ViewSonic ViewBoard  
6532-2**

Cena

**0,00 zł**

Producent

**ViewSonic**

## OPIS PRODUKTU

### Display

Panel Size: 65"

Panel Type: TFT LCD Module with DLED Backlight.

Display Area (mm): 1428.48(H)x 803.52 (V) (64.5" diagonal)

Aspect Ratio: 16:9

Resolution: UHD 3840x2160(Pixels)

Colors: 1.07B colors (8bit+FRC)

Brightness: 350 nits (typ.)

Contrast Ratio: 4000:1

Response Time: 6.5ms

Viewing Angles: H=178, V=178typ.

Backlight Life: 30,000 Hours (Min)

Surface Treatment: Hardness: 9H Anti-glare coating

Orientation: Landscape

### Platform

Processor: ARM quad-core Cortex-A55

RAM: 4GB DDR4

Storage: 32 GB

### Touch

Type/ Tech: Ultra Fine Touch Technology

Touch Point: 20 points touch, 2 points writing

### INPUT

HDMI: HDMI 2.0 x2 (3840x2160 @60Hz)

RGB / VGA: x1

Audio: x1

RS232: x1

OPS: x1 (Optional Intel Standard OPS)

WiFi: x1 (Optional VB-WIFI-002/VB-WIFI-004)

### OUTPUT

Audio: x1

LAN  
RJ45: x1  
USB  
Type A: USB2.0 Front x2; Side x2  
Type B: x1 for HDMI/VGA touch  
SPEAKERS  
10W x 2  
Top Camera Plate  
Yes  
Embedded OS  
Android 9  
Bundle Software  
Basic Annotation Software: myViewBoard Whiteboard  
Pro Annotation Software: myViewBoard Whiteboard for Windows (Embedded in optional Windows Slot-in PC)  
Wireless Presentation: myViewBoard Display & ViewBoard Cast  
Special Features  
All-in-one USB port: (combine slot-in PC/Android/HDMI USB port) Front "SmartPort™ USB" to all channels.  
Simple LAN sharing between IFP and slot-in device: 10/100M for Android & Slot-in PC  
Light Sensor: Yes  
Power  
Voltage: 162V-264V +/- 10%  
Consumption: On: 175W(typ.)  
Off: ≤ 0.5W  
ERGONOMICS  
Wall Mount (VESA® ): 600\*400  
OPERATING CONDITIONS  
Temperature (° C): 0°C to 40°C  
Humidity: 10% ~ 90% RH non-condensing  
DIMENSIONS (W x H x D)  
Physical (inch / mm): 1489×897×87 mm / 58.6x35.3x3.4 in  
Packaging (inch / mm): 1628×208×1005 mm / 64x8.2x39.5 in  
WEIGHT  
Net (lb / kg): 38.3kg/84.4lb  
Gross (lb / kg): 46.0kg/101.4lb  
REGULATIONS  
EMC/CE , CB/LVD, GOST-R / EAC, FAC, RCM, BIS, ECAS, LBL (Low Blue Light Certification), RoHS, REACH, SCIP, WEEE, TPCH, Packing waste, CA65, Green BOM, ErP-Eco  
PACKAGE CONTENTS  
1. Power cord / 2.Remote control with AAA battery / 3.USB touch cable / 4. Touch pen x 2 / 5. Quick Start Guide + Compliance statement / 6. RS232 adapter / 7. Screw x 4 ( wall mount 4) / 8. HDMI cable / 9. Clamp x5 / 10. Camera plate x1  
Compatible Slot-in PC  
VPC12-WPO/VPC25/VPC2C/VPC27 series