

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Nazwa	<b>Monitor interaktywny ViewBoard IFP6552-1B</b>
Cena	<b>10 419,00 zł</b>
Producent	<b>ViewSonic</b>

## OPIS PRODUKTU

### SPECIFICATIONS

#### Display

Panel Size: 65"

Panel Type: TFT LCD Module with DLED Backlight.

Display Area (mm): 1428.48(H) x 803.52(V)

Aspect Ratio: 16:9

Resolution: UHD 3840x2160(Pixels)

Colors: 1.07B colors (10bit)

Brightness: 400 nits (typ.)

Contrast Ratio: 1200:1 Typ. , 5000:1 Max.(DCR enable)

Response Time: 8ms

Viewing Angles: H = 178, V = 178 typ.

Backlight Life: 50,000 Hours (Typ.)

Surface Treatment: Hardness: 7H (9H pencil), Anti-flare coating

#### Platform

Processor: ARM Cortex A73\*4

RAM: 4GB (IFP6552-1A)8GB (IFP6552-1B)

Storage: 32GB (IFP6552-1A)64GB (IFP6552-1B)

#### Touch

Type/ Tech: UFT (Ultra Fine Touch) Technology

Touch Resolution: 32767 x 32767

Touch Point: Windows: 33 points touchAndroid: 20 points touch

## INPUT

HDMI: x2 (3840x2160@60Hz, HDCP2.2, CEC, Front x1, Side x1)x1 (3840x2160@60Hz, HDCP2.2, CEC, ARC, Side x 1)

RGB / VGA: x1 (1920x1080 @60Hz)

DisplayPort: x1 (3840x2160 @60Hz)

Audio: x1 (PC audio in)

RS232: x1

OPS: module slot x 1

WiFi: module slot x 1

## OUTPUT

HDMI: x1 (on demand)

Audio: x1 (Earphone out)

SPDIF: x1 (optical)

LAN

RJ45: x1

USB

Type A: USB 2.0 x 1(Side x1)USB 3.0 x 4 (Front x2, Side x2, SmartPort™ USB)

Type B: x2, for touch

Type C: x1 (USB3.0, DP1.2 Alt Mode, Ethernet, PD 60W)

## SPEAKERS

15W x 2 + 15W x 1 subwoofer

## MICROPHONE

built-in 8-array microphone

Top Camera Plate

Yes

Embedded OS

Android 9

Bundle Software

Basic Annotation Software: myViewBoard WhiteBoard for Android

Pro Annotation Software: myViewBoard WhiteBoard for Windows (embedded in VPC)

Wireless Presentation: ViewBoard Cast & myViewBoard Display

## Special Features

All-in-one USB port (combine Windows/Android USB port; no need to distinguish them anymore): USB 3.0 x 4

Simple LAN sharing between IFP and slot-in device: 10/100/1000M for Android and PC

Light Sensor: Yes

## Power

Voltage: 100-240VAC +/- 10% Wide Range

Consumption: 190W (Typ.) < 0.5 W ("Off")

## ERGONOMICS

Wall Mount (VESA® ): 600 x 400

## OPERATING CONDITIONS

Temperature (° C): 0°C to 40°C

Humidity: 20% ~ 80% RH Non-Condensing

## DIMENSIONS (W x H x D)

Physical (inch / mm): 1509.1 (W) x 955.4 (H) x 119.1 (D) mm 59.41 (W) x 37.61 (H) x 4.69 (D) inch

Packaging (inch / mm): 1660 (W) x 1045 (H) x 245 (D) mm 65.35 (W) x 41.14 (H) x 9.65 (D) inch

## WEIGHT

Net (lb / kg): 96.78 lb / 43.9 kg

Gross (lb / kg): 122.14 lb / 55.4 kg

## REGULATIONS

cTUVus, FCC, EPEAT, Mexico coc, Mexico Energy, RoHS, Energy Star 8, CEC, EMC/CE, CB, RoHS & DOC, REACH, WEEE, ErP. EEI, RCM, BIS, PSE, VCCI, CCC, CECP

## PACKAGE CONTENTS

1. Power cable(3 meters) 2. Remote control 3. USB Type-C cable (1.5 meters) 4. USB Touch cable (3

meters, USB2.0) 5. Touch pen x 2 6. Quick Start Guide + Compliance statement 7. RS232 adapter 8. Clamp x 5 9. Camera Plate 10. Screw x 8 (camera 2+2, wall mount 4) 11. HDMI cable (3 meters) 12. Eraser 13. AAA Battery x 2  
Compatible Slot-in PC  
VPC12 & VPC25/27-O & VPC25/27-O-B series