
Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



ViewSonic
See the difference™ 

Nazwa **Monitor interaktywny ViewSonic IFP6560**

Cena **18 999,00 zł**

Producent **ViewSonic**

OPIS PRODUKTU

INTERNAL SPEAKERS

VESA® Wall Mount 600 x 400 mm

MENU CONTROLS

USB 2.0 x 2

HDMI 1.4 IN

USB B TOUCH PORT

MIC

POWER ON / OFF

FIPS201 CERTIFIED FINGERPRINT READER

DISPLAY PORT

HDMI 2.0 In X 2

USB TOUCH PORT

USB 3.0 X 2

USB 2.0

HDMI OUT

AUDIO IN

VGA IN

LAN

RS232 IN

SPDIF

EARPHONE

Intel Unite® Certified OPS Slot

PARAMETRY:

DISPLAY

Panel Size : 65"

Type/Tech : TFT LCD Module with DLED Backlight

Display Area (mm) : 1428.48(H) x 803.52(V) mm (64.5" diagonal)

Aspect Ratio : 16:9

Native Resolution : UHD 3840x2160(Pixels)

Colors : 16.7M (8bit)

Brightness : 350 nits (typ.)

Contrast Ratio : 4000:1 Typ.

Response Time : 8ms

Viewing Angles : H = 178, V = 178 typ.

Backlight Life : 30,000 Hours (Min)

Surface Treatment : AG G2

Bezel : Slim

Orientation : Landscape

TOUCH

Type/ Tech : Flatfrog InGlass technology P-series

Touch Resolution : 22855X12856

Touch Point : 20 points touch

INPUT

HDMI : 1.4a x1 (3840x2160@30Hz); 2.0 x2 (3840x2160@60Hz)

RGB / VGA : x1

DisplayPort : x1(3840x2160@30Hz)

Audio : x1 (PC Audio in)

RS232 : x1

OPS : x1 PC Slot (Intel OPS Standard)

OUTPUT

RGB / VGA : Refer to timing table

HDMI : x1(1080p, 4K@60hz)

Audio : x1 (Earphone out)

SPDIF : x1

RS232 : x1

LAN

RJ45 : x1

USB

Type A : USB 2.0 x3 (including 2 USB port in front); USB 3.0 x2

Type B : x2, for touch

SPEAKERS

10 Wx2

CAMERA PLATE ON TOP FOR SREW-IN WEBCAM INSTALLATION

Yes (Support external Logitech Meet-up)

COMPATIBILITY

RGB PC/HDMI PC : Refer to timing table

HDMI : 3840x2160

EMBEDDED OS

Android 5.0.1

USB SUPPORTED FILE FORMAT

Picture -

MBP, JPG, JPEG

Video -

Codec: MPEG1/2, MPEG4, H.263, H.264, MVC, AVS, AVS+, WMV3, VCI, Motion JPEG, VP8, VP9

Container: MPEG PROGRAM STREAM, MPEG TRANSPORT STREAM, MP4, 3GPP, AVI, MKV, ASF, WMV,

WEBM

Audio -

Codec: MPEG 1/2, AAC

BUNDLE SOFTWARE

Basic Annotation Software : vBoard

Pro Annotation Software : myviewboard for Windows (Pre-install in VPC12-WPO-3)

Wireless Presentation With Touch Feedback: Viewboard Cast : Yes

Screen Split: ViewSplit (Windows Based) : Yes (download from ViewSonic website)

Zoom : Yes

ViewSonic Launcher : Embedded

SPECIAL FEATURES

All-in-one USB Port (combine Windows/Android USB Port; No Need To Distinguish Them Anymore)

: Front USB SmartPort™ to all channels

One Click To Cloud Drive : Integrate into side tool bar

Simple LAN Sharing Between IFP And Slot-in Device : Yes

POWER

Voltage : 100V-240V,50/60Hz (AC)

Consumption : Operation:

210W (typ) - without OPS

270W (typ.) -with OPS

≤ 0.5 W ("Off")

*Max power consumption from OPS doesn't over 60W.

ERGONOMICS

Wall Mount (VESA®) : 600 x 400

OPERATING CONDITIONS

Temperature (° C) : 0°C to 40°C

Humidity : 20% ~ 80% RH non-condensing

DIMENSIONS (W X H X D)

Physical (inch / Mm) : 61.63x3.72 x 38.07 in/ 1565.5x967.1x94.5 mm

Packaging (inch / Mm) : 67.52x11.02x40.31 in/1715x280x1100 mm

WEIGHT

Net (lb / Kg) : 106.9 lb / 48.5 Kg

Gross (lb / Kg) : 134.5 lb / 61 Kg

REGULATIONS

FCC, CE, cTUVus,CB, RoHS, WEEEFCC, CE, cTUVus,CB, RoHS, WEEE, ES7.1

PACKAGE CONTENTS

1. HDMI cable(1.5 meters)
2. Power cable(3 meters) x 4 (A+E+M+U)
3. Remote control with AA battery
4. USB cable(1.8 meters)
5. Touch pen x 2
6. Quick Start Guide & Compliance statement
7. Webcam Plate
8. Wall mount Screw x 4

COMPATIBLE SLOT-IN PC

VPC12-WPO-2 (Intel i5-6300U with vPro+Win10 Pro 64 bit)