


## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Nazwa

**Monitor interaktywny ViewSonic  
ViewBoard IFP7550-5F**

Cena

**0,00 zł**

Producent

**ViewSonic**

## OPIS PRODUKTU

### Display

Panel Size: 75"

Panel Type: TFT LCD Module with DLED Backlight. IPS

Display Area (mm): 1650.24(H) × 928.26(V)

Aspect Ratio: 16:9

Resolution: UHD 3840x2160

Colors: 1.07B colors (10bit)

Brightness: 400 nits (typ.), 450 nits (max.)

Contrast Ratio: 1200:1 (typ.) 5000:1 (DCR)

Response Time: 8ms

Viewing Angles: H = 178, V = 178 typ.

Backlight Life: 50,000 hours(Min)

Surface Treatment: Hardness: 7H, Anti-glare coating

Bezel: Slim

Orientation: Landscape

Platform

Processor: ARM Cortex-A73\*4 + Cortex-A53\*4

RAM: 8GB

Storage: 64GB

Touch

Type/ Tech: Ultra Fine Touch Technology (IR Recognition)

Touch Resolution: 32768 × 32768

Touch Point: Windows: 40 points of touch, Android : 20 points of touch

INPUT

HDMI: 2.0 x 3 (3840x2160 @60Hz, HDCP2.2, HDMI1 with CEC/ARC)

RS232: x1

OPS: x1

WiFi: x 1 module slot

OUTPUT

HDMI: x1 (4K@60Hz)

Audio: x1 (Earphone out)

SPDIF: x1 (optical)

LAN

RJ45: x2

USB

Type A: 2.0 x 2

3.0 x 4

Type B: x2, for touch

Type C: x1 ( DP 1.2, USB2.0, PD65W, Ethernet 100M)

SPEAKERS

15W x 2 + 16W x 1 subwoofer

Top Camera Plate

Yes

Embedded OS

Android 11

Bundle Software

Basic Annotation Software: myViewBoard

Pro Annotation Software: myViewBoard for Windows (Embedded in Windows Slot-in PC)

Wireless Presentation: vCast/myViewBoard Display App

Special Features

All-in-one USB port: "SmartPort™ USB" to all channels.

Simple LAN sharing between IFP and slot-in device: Yes

Light Sensor: Yes

Power

Voltage: 100-240VAC +/- 10% Wide Range

Consumption: 135W(typ.), 0.5W (off)

ERGONOMICS

Wall Mount (VESA® ): 800 mm x 400 mm

OPERATING CONDITIONS

Temperature (° C): 0°C to 40°C

Humidity: 10% ~ 90% RH non-condensing

DIMENSIONS (W x H x D)

Physical (inch / mm): 67.3 x 40.2 x 3.5 in / 1710 x 1020 x 90 mm

Packaging (inch / mm): 76.0 x 44.9 x 11.0 in / 1930 x 1140 x 280 mm

WEIGHT

Net (lb / kg): 118.8lb/53.9kg

Gross (lb / kg): 158.5lb/71.9kg

REGULATIONS

cTUVus, FCC/ICES003, Energy Star 8.0, EMC/CE, CB/LVD, GOST-R/EAC, UkrSEPRO, EPEAT, Mexico NOM ,

Mexico Energy, UKCA, UK-EEL, BSMI, BIS, LBL( Low Blue Light Certification), Flicker Free, Green BOM,

RoHS, ErP-Eco, REACH, SCIP, WEEE, TPCH , Packing waste, CA65, PAIA

PACKAGE CONTENTS

1. Power cord

2. Remote control with AAA battery

3. Touch USB cable

4. Touch pen x 2

(VB-PEN-009)

5. Quick Start Guide + Compliance statement

6. RS232 adapter

7. Clamp x 5

8. Camera Plate

9. Screw x 8

10. HDMI cable

Compatible Slot-in PC

- VPC25-W33-O1-1B

- VPC25-W53-O1-1B

- VPC27-W53-O1-1B

- VPC27-W55-O2-1B