

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Nazwa **Monitor interaktywny ViewSonic
ViewBoard IFP8670**

Cena **0,00 zł**

Producent **ViewSonic**

OPIS PRODUKTU

Złącza komunikacyjne i wymiary:

Sensor Hub

Camera

6 Array Microphone

Meun Controls

Smart Pen and Charger

Intel Unite® Certified OPS Slot

USB-C

(USB 3.0, DP 1.4 Alternate Mode, Ethernet, PD 60W)

HDMI Out

HDMI In

USB 3.0 X 3

Touch X 2

Display Port

WiFi Module Slot

VESA Wall Mount

800x600mm

2.1 Speakers

SPDIF

RS232

Audio Out

LAN

USB 2.0

PARAMETRY:

DISPLAY

Panel Size: 86"

Type/Tech: TFT LCD Module with DLED Backlight.

Display Area (mm): 1895.04 (H) x 1065.96 (V) (85.6" diagonal)

Aspect Ratio: 16:9
Native Resolution: UHD 3840x2160(Pixels)
Colours: 1.07B colours (10bit)
Brightness: 350 nits (typ.)
Contrast Ratio: 1200:1 Typ.
Response Time: 8ms
Viewing Angles: H = 178, V = 178 typ.
Backlight Life: 30,000 Hours (Min)
Surface Treatment: Anti-Glare/anti finger print
Bezel: Slim
Orientation: Landscape
PLATFORM
Processor: Dual core A73+Dual core A53
RAM: 4GB DDR4
Storage: 32GB
TOUCH
Type/ Tech: PCAP
Touch Resolution: 32767 x 32767
Touch Point: 20 points touch, 10 points writing

INPUT

HDMI: 2.0 x1 (3840x2160 @60Hz)
DisplayPort: X1 1.4
RS232: x1
OPS: x1 PC Slot (proprietary)

OUTPUT

HDMI: X1(4K2K@60Hz)
Audio: x1 (Earphone out)
SPDIF: 1(optical)

LAN

RJ45: x1

USB

Type A: USB 3.0 x3
Type B: USB 3.0 x2, for touch
Type C: x1 USB3.0, DP1.4 Alternate mode, Ethernet, PD 60W

SPEAKERS

SPEAKERS: 10W x 2 + 15W x 1 subwoofer

CAMERA PLATE ON TOP FOR SCREW-IN WEBCAM INSTALLATION

Camera plate on top for screw-in webcam installation: Yes

COMPATIBILITY

CVBS: 480i

HDMI: 3840x2160

EMBEDDED OS

Embedded OS: Android 8

USB SUPPORTED FILE FORMAT

USB SUPPORTED FILE FORMAT: Picture -

BMP, JPEG, PNG

Video -

Codec: MPEG1, MPEG2, MPEG2-PS, MPEG4, MKV

Container: MPG, MP4, MOV, VOB, DAT, MKV

Audio -

Codec: AAC, HEAAC, MPEG1, MPEG2

Container: AAC, M4A, MP3

BUNDLE SOFTWARE

Basic Annotation Software: myViewBoard for android

Pro Annotation Software: myViewBoard for windows (Embedded in Windows Slot-in PC)

Wireless Presentation with Touch Feedback: Viewboard Cast: Yes

Zoom: Yes

ViewSonic Launcher: Embedded

SPECIAL FEATURES

All-in-one USB port (combine Windows/Android USB port; no need to distinguish them anymore): Yes

Simple LAN sharing between IFP and slot-in device: Yes

POWER

Voltage: 100-240VAC +/- 10% Wide Range

Consumption: On:176.6W(Typ.)

Off: <0.5W

ERGONOMICS

Wall Mount (VESA®): 800 x 600

OPERATING CONDITIONS

Temperature (° C): 0°C to 40°C

Humidity: 10% ~ 90% RH non-condensing

DIMENSIONS (W X H X D)

Physical (inch / mm): 1962X1146X84(mm)

77.24x45.11x3.3(inch)

Packaging (inch / mm): 2123X1345X280(mm)

83.8X52.9X11(inch)

WEIGHT

Net (lb / kg): 160.93/73Kg

Gross (lb / kg): 209.43/95Kg

REGULATIONS

REGULATIONS: FCC, cTUVus, CB, CE, RCM,

ENERGY STAR VERSION

Energy Star version: Under proceed apply to ES8.0

EEL RATING

EEL rating: A+

PROAV CERTIFICATE READINESS

Crestron: 75%

Extron: 20%

AMX: 0%

PACKAGE CONTENTS

PACKAGE CONTENTS: 1. Power cable(3 meters) x 4

2. Remote control

3. AAA battery X2

4. USB cable Type C(1.5 meters pass logo)

5. activeTouch pen x 2

6. Pen Charger X1

7. Quick Start Guide

8. RS232 adapter

9. Clamp x 7

10. Camera

11. Screw x 6 (4 for wall mount ,2 for sensor hub)

12. HDMI cable -3M

13. Sensor hub

14 .Touch USB cable 3M

15. Micro USB cable for camera 2M

COMPATIBLE SLOT-IN PC

Compatible Slot-in PC: VPC14-WP series

VPC10-WP series

VPC15-WP series

VPC16-WP series

VPC17-WP series