

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



ViewSonic
See the difference™

Nazwa **Monitor profesjonalny ViewSonic
VP2785-2K**

Cena **0,00 zł**

Producent **ViewSonic**

OPIS PRODUKTU

SPECIFICATIONS

DISPLAY

Display Size (in.): 27

Viewable Area (in.): 27

Panel Type: IPS Technology

Resolution: 2560 x 1440

Resolution Type: QHD

Static Contrast Ratio: 1,000:1 (typ)

Dynamic Contrast Ratio: 20M:1

Light Source: LED

Brightness: 300 cd/m2 (typ)

Colours: 1.07B

Colour Space Support: 10 bit (8 bit + A-FRC)

Aspect Ratio: 16:9

Response Time (Typical GTG): 5ms

Viewing Angles: 178° horizontal, 178° vertical

Backlight Life (Hours): 30000 Hrs (Min)

Curvature: Flat

Refresh Rate (Hz): 60

Blue Light Filter: Yes

Flicker-Free: Yes

Colour Gamut: Adobe RGB: 114% size / 100% coverage (Typ)

EBU: 152% size / 100% coverage (Typ)

REC709: 154% size / 100% coverage (Typ)

SMPTE-C: 166% size / 100% coverage (Typ)

NTSC: 109% size (Typ)

sRGB: 154% size / 100% coverage (Typ)

Pixel Size: 0.233 mm (H) x 0.233 mm (V)

Surface Treatment: Anti-Glare, Hard Coating (3H)

COMPATIBILITY

PC Resolution (max): 2560x1440

Mac® Resolution (max): 2560x1440

PC Operating System: Windows 7/8/8.1/10 certified; macOS tested

Mac® Resolution (min): 2560x1440

USB 3.1 Type A: 3

USB 3.1 Type B: 1

USB 3.1 Type C: 1

3.5mm Audio Out: 1

HDMI 1.4: 1

Display Port: 1

Display Port Out: 1

Power in: External power adapter

POWER

Eco Mode (Conserve): 29.85W

Eco Mode (Optimised): 34.71W

Consumption (typical): 40.46W

Consumption (max): 52.98W

Voltage: AC 100-240V, 50/60 Hz

Stand-by: 0.5W

Power Supply: External

ADDITIONAL HARDWARE

Kensington Lock Slot: 1

Cable Organisation: Yes

CONTROLS

Physical Controls: Key 1, Key 2, Key 3, Key 4, Key 5, Key 6 (power)

On Screen Display: Input Select, Audio Adjust, ViewMode, Colour Adjust, Manual Image Adjust, Setup Menu

OPERATING CONDITIONS

Temperature: 32°F to 104°F (0°C to 40°C)

Humidity (non-condensing): 20% to 90%

WALL MOUNT

VESA Compatible: 100 x 100 mm

INPUT SIGNAL

Frequency Horizontal: 15 ~ 130KHz

Frequency Vertical: 24 ~ 120Hz

VIDEO INPUT

Digital Sync: TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2), Micro-Packet - Type C

ERGONOMICS

Height Adjust (mm): 130

Swivel: 120°

Tilt (Forward/Back): -5° / 21°

Pivot (Right/Left): 90° / 90°

WEIGHT (METRIC)

Net (kg): 6.7

Net Without Stand (kg): 4.1

Gross (kg): 10.2

DIMENSIONS (METRIC) (WXHxD)

Packaging (mm): 720 x 460 x 268

Physical (mm): 612 x 545 x 215

Physical Without Stand (mm): 612 x 363 x 57

GENERAL

Regulations: cTUVus, FCC-B, ICES003, CEC, NRCAN, MX-CoC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, BSMI, RCM, CCC, China RoHS, CEL

PACKAGE CONTENTS: VP2785-2K x1, 3-pin Mickey Mouse Plug (IEC C5) x1, DisplayPort Cable (v1.2; Male-Male) x1, USB3.1 Up Stream Cable(cable length :1.8M), AC/DC Adapter x1, Quick Start Guide x1

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

Warranty: *Warranty offered may differ from market to market