

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



ViewSonic 
See the difference™

Nazwa **Monitor profesjonalny ViewSonic
VP2785-4K**

Cena **5 225,00 zł**

Producent **ViewSonic**

OPIS PRODUKTU

PARAMETRY:

SPECIFICATIONS

DISPLAY

Monitor Size: 27"W (27" Viewable)

Panel Technology: AH-IPS panel

Resolution: UHD 3840 x 2160

Display Area: 596.74mm (H) x 335.66mm (V)

Aspect Ratio: 16:9

Brightness: 350 cd/m2 (Typ)

Contrast Ratio: 1000:1 (Typ)

Dynamic Contrast Ratio: 20,000,000:1

Viewing Angle: 178 degrees / 178 degrees (Typ)

Refresh Rate: 60Hz

Response Time: GTG(AVG): 5 ms

Colours: 1.07 Billion colours, 10bit with FRC

Colour Gamut: Adobe RGB: 99% Coverage

NTSC: 72.5% Coverage

sRGB: 100% Coverage

REC709: 100% Coverage

SMPTE-C: 100% Coverage

EBU: 100% Coverage

DCI-P3: 95.1% Coverage

*colour gamut coverage may vary 1% depending on colour mode.

Pixel Size: 0.1554mm (H) x 0.1554mm (V)

INPUT SIGNAL

Frequency: HDMI/ DisplayPort/ mini DP/ Type-C: Fh = 15 ~ 204KHz ; Fv = 24 ~ 120Hz

Sync: HDMI: TMDS

DisplayPort/ mini DP/ Type-C: PCI-E

COMPATIBILITY

PC: PC Compatibles (3840 x 2160) HDMI/DisplayPort Non-Interlaced)

Mac®: Power Mac (up to 3840 x2160) HDMI/DisplayPort)

CONNECTOR

Digital: DisplayPort 1.4 HDR ready x 1

Mini DP 1.4 HDR ready x 1

HDMI 2.0 x 2

Audio Out: 3.5mm Mini Phone Jack Audio out x 1

USB

USB3.1 Gen 1 Type C upstream x1 and Type B upstream x1

USB3.1 Gen 1 Type A downstream x 3

POWER

Power: 7.4 x 5.1 x 10 External DC connector

Voltage: AC 100-240V (Universal); 50/60Hz

Consumption: 67W

Optimise: 55W

Conserve: 45W

MODEL COLOUR

Black

ERGONOMICS

Tilt: -5.0° ~ 21.0°

Swivel: 120°

Pivot: 0~90 degree (Clockwise and Counter Clockwise)

Height Adjustment: 0~130mm

WALL MOUNT

VESA®: 100mm x 100mm

OPERATING CONDITIONS

Temperature (° F / ° C): 32°F to 104°F (0°C to 40°C)

Humidity: 20% to 90% (no condensation)

DIMENSIONS (W X H X D) (MM)

Physical with stand (mm): 612.4 mm (W) x 545.51 mm (H) x 214.96 mm (D)

Physical without stand (mm): 612.4mm (W) x 362.7 mm (H) x 57.08 mm (D)

Packaging (mm): 720 mm (W) x 268 mm (H) x 460 mm (D)

WEIGHT

Net with stand (kg): 6.4 kg

Net without stand (kg): 3.92 kg

Gross (kg): 10.13 kg

REGULATIONS

cTUVus, FCC-B, ICES003, CEC, MX-CoC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, VCCI,

PSE, KC, e-Standby, CCC, China RoHS, CEL

PACKAGE CONTENTS

LCD Display

AC/DC Adapter

Power Cable(cable length :1.8M)

Mini DP to DisplayPort Cable (cable length :1.8M)

USB3.1 Gen 1 Type-C Cable(cable length :1.8M)

USB3.0 Up Stream Cable(cable length :1.8M)

Quick Start Guide

ViewSoinc Wizard CD-ROM

*Actual content may differ from market to market