

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



**ViewSonic**  
See the difference™

Nazwa	<b>Monitor Viewsonic 42" Full HD Commercial Display CDP4235</b>
Cena	<b>0,00 zł</b>
Producent	<b>ViewSonic</b>

## OPIS PRODUKTU

### SPECIFICATIONS

#### COLORS

Black

#### LCD

Type : 42" colour TFT active matrix, wide LCD

Contrast Ratio : 4000:1 (typ)

Viewing Angles : 178° horizontal, 178° vertical

Brightness : 450 cd/m2(typ)

Display Area : 36.6" horizontal x 20.6" vertical; 42" diagonal

Optimum Resolution : 1920 x 1080, 435mm dot pitch

Response Time : 8ms

Light Source : 50,000 hrs. (typ)

Aspect Ratio : 16:9

Panel Surface : Anti-glare, hard coating (3H)

#### DIMENSIONS

Physical With Stand : 39.04" x 25.38" x 11.24"

(991.6mm x 621mm x 328.8mm)

Physical Without Stand : 39.04" x 25.5" x 1.47"

(991.6mm x 115.5mm x 25.5mm)

#### PACKAGE CONTENTS

LCD display, power cable, remote control with batteries, User Guide CD

#### INPUT

Video Input : HDMI, DVI, component, VGA, S-Video, composite

Video Output : VGA, component, DVI

Control Input/Output : RS-232/RJ45

#### INPUT SIGNAL

TV/Video Comp. : 480i, 480p, 720p, 1080i, 1080p

#### CONNECTOR

Digital : HDMI, DVI

Power : 3-pin plug

Analog : 9-pin mini D-sub (VGA)

#### POWER

Voltage : AC 100–240V (universal), 50–60Hz

Consumption : 210W (typ)

#### CONTROLS

Picture : Picture mode, contrast, brightness, colour temperature, temperature adjust, sharpness

Front Panel : Power, Exit, +, –, Menu/Enter

Special : Aspect ratio, over scan, power save, image retention, auto adjustment, monitor ID, reset

Audio : Volume, mute, audio source

Diagnostic : Thermal, back light, ambient, 5V detect, 12 detect

Input : VGA, DVI, HDMI, YPbPr

OSD Setting : Languages, OSD H. position, OSD V. position, OSD timer

VGA Setting : Auto adjustment, clock, phase, sharpness, H. position, V. position

#### VESA MOUNT COMPLIANT

VESA 400mm x 400mm

#### WEIGHT

Net With Stand : 51.8 lb. (23 kg)

Net Without Stand : 50.7 lb. (23 kg)

Gross With Stand : 61.7 lb. (28 kg)

#### OPERATING CONDITIONS

Humidity : 10–80% (non-condensing)

Temperature (landscape) : 32–104°F (5–40°C)

Temperature (portrait) : 32–95°F (5–35°C)

#### RECYCLE/DISPOSAL

The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws.

#### AUDIO OUT

Speakers : 2 x 10w