

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Nazwa

**Monitor Viewsonic 55" Full HD Ultra  
Narrow Bezel Display CDX5550-L**

Cena

**0,00 zł**

Producent

**ViewSonic**

## OPIS PRODUKTU

LCD

Type

55" (54.6" viewable) color TFT active matrix, wide LED

Display Area

47.6" horizontal x 26.7" vertical; 54.6" diagonal

Optimum Resolution

1920x1080, 0.485mm dot pitch

Contrast Ratio

3500:1 (typ)

Viewing Angles

178° horizontal, 178° vertical

Response Time

8ms

Light Source

Long life, 50,000 hrs. (typ)

Brightness

700 cd/m2 (typ)

Aspect Ratio

16:9

Panel Surface

Anti-glare, hard coating (3H)

Dynamic Contrast Ratio

N/A  
INPUT  
PC  
N/A  
TV  
480i, 480p, 720p, 1080i, 1080p  
Video Input  
HDMI, DVI, component, VGA, S-Video, CVBS (BNC)  
Video Output  
VGA, component  
Audio  
N/A  
Frequency  
N/A  
Sync  
N/A  
Digital  
N/A  
Tuner  
N/A  
Control Input Output  
RS-232 / RJ45  
DISPLAY  
Touch  
N/A  
AUDIO  
Speakers  
Internal 10-watt (x2) / 8 ohm  
Amplifier  
10-watt (x2) / 8 ohm  
CONNECTOR  
Analog  
9-pin mini D-sub (VGA)  
Digital  
HDMI, DVI  
Power  
3-pin plug  
POWER  
Voltage  
AC 100–240V (universal), 50–60Hz  
Consumption  
220W (typ)  
CONTROLS  
Screen  
N/A  
Input  
VGA, DVI, HDMI, YPbPr  
Basic  
N/A  
Picture  
Picture mode, contrast, brightness, color temperature, temperature adjust, sharpness  
Audio  
Volume, mute, audio source  
Sound  
N/A

## OSD

Languages, OSD H. position, OSD V. position, OSD timer

## Panel

Power, Exit, +, -, Menu/Enter

## VGA Setting

Auto adjustment, clock, phase, sharpness, H. position, V. position

## Special

Aspect ratio, over scan, power save, image retention, auto adjustment, monitor ID, reset

## Diagnostic

Thermal, back light, ambient, 5V detect, 12 detect

## Set Up

N/A

## TV

N/A

## Advanced Options

N/A

## OPERATING CONDITIONS

### Humidity

10–90% (non-condensing)

### Temperature(landscape)

32–104°F (0–40°C)

### Temperature(Portrait)

32–95°F (0–35°C)

## DIMENSIONS (WxHxD)

### Physical Without Stand

47.9 x 27.0 x 5.0 in. / 1259.3 x 686.1 x 128.1 mm

### Physical With Stand

47.9 x 29.1 x 15.8 in. / 1259.3 x 737.8 x 400 mm

## WEIGHT

### Gross

94.8 lb. / 43.0 kg

### Net Without Stand

79.4 lb. / 36.0 kg

### Net With Stand

84.2 lb. / 38.2 kg

## Regulations

FCC, ICES003, UL, cUL, CE, CB, C-Tick, BSM

## Wall Mount

VESA® 400mm x 400mm

## Recycle/Disposal

The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws.

## PACKAGE CONTENTS

CDX5550-L LED Display, power cable, remote control with batteries, User Guide, Quick Start Guide

Optional Accessories (sold separately)

N/A

## Warranty

Three-year limited warranty on parts, labor and backlight