

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



ViewSonic
See the difference™

Nazwa **Monitor Viewsonic Commercial LCD
Display CDP6530**

Cena **0,00 zł**

Producent **ViewSonic**

OPIS PRODUKTU

SPECIFICATIONS

COLORS

Black

LCD

Type : 65" (64.6" viewable) colour TFT active matrix, wide LCD

Contrast Ratio : 5000:1 (typ)

Viewing Angles : 178° horizontal, 178° vertical

Brightness : 500 cd/m2 (typ)

Display Area : 56.2" horizontal x 31.6" vertical; 64.6" diagonal

Optimum Resolution : 1920 x 1080, 600mm dot pitch

Response Time : 8ms

Light Source : Long life, 50,000 hrs. (typ)

Aspect Ratio : 16:9

Panel Surface : Anti-glare, hard coating (3H)

DIMENSIONS

Physical (WxHxD) : 59.3" x 35.4" x 5.3" (W x H x D) (1500mm x 900mm x 136mm)

PACKAGE CONTENTS

LCD display, power cable, remote control with batteries,

User Guide CD

AUDIO

Amplifier : 12-watt / 8 ohm

INPUT

Video Input : HDMI, DVI, component, VGA, S-video, CVBS (BNC)

Video Output : VGA, component, DVI (Loop through)

Control Input/Output : RS-232

INPUT SIGNAL

TV/Video Comp. : 480i, 480p, 720p, 1080i, 1080p

CONNECTOR

Digital : HDMI, DVI, S-video YPbPr, CVBS

Power : 3-pin plug

Analog : 15-pin mini D-sub (VGA)

POWER

Voltage : AC 100–240V (universal), 50–60Hz

Consumption : 520W (typ)

CONTROLS

Picture : Picture mode, contrast, brightness, colour temperature, temperature adjust, sharpness

Front Panel : Power, Exit, +, –, Menu/Enter

Special : Aspect ratio, over scan, power save, image retention, auto adjustment, monitor ID, reset

Audio : Volume, mute, audio source

Diagnostic : Thermal, back light, ambient, 5V detect, 12 detect

OSD Setting : Languages, OSD H. position, OSD V. position, OSD timer

VGA Setting : Auto adjustment, clock, phase, sharpness, H. position, V. position

OPTIONAL ACCESSORIES AVAILABLE

Stand (optional), Wall Mount (WMK-013),

Wall Mount with Locking Media Player Cradle (WMK-028)

VESA MOUNT COMPLIANT

VESA 200mm x 400mm, 400mm x 400mm

WEIGHT

Gross : 176.4 lb. (80.0 kg)

Net : 154.3 lb. (70.0 kg)

OPERATING CONDITIONS

Humidity : 20–90% (non-condensing)

Temperature (landscape) : 32–104°F (0–40°C)

Temperature (portrait) : 41–95°F (5–35°C)

RECYCLE/DISPOSAL

The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws.

AUDIO OUT

Speakers : Internal 12-watt (x2)

RESOLUTIONS

640 x 480 at 60 Hz to 75 Hz

800 x 600 at 60 Hz, 60Hz to 75 Hz

1024 x 768 at 60 Hz, 60Hz to 75 Hz

1280 x 768 at 60 Hz, 60Hz to 75 Hz

1360 x 768 at 60 Hz, 60Hz to 75 Hz

1280 x 1024 at 60Hz

1600 x 1200 at 60 Hz

1920 x 1080 at 60Hz (recommended resolution)

NTSC, SECAM, 4.43 NTSC

Component: 480i,480p,720p,1080i,1080p

OPS

Open Pluggable Specification slot (OPS) ready