

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



**ViewSonic**  
See the difference™

Nazwa

**Monitor Viewsonic Slim Commercial LED  
Display CDP4237-L**

Cena

**0,00 zł**

Producent

**ViewSonic**

## OPIS PRODUKTU

### SPECIFICATIONS

#### COLORS

Black

#### LCD

Type : 42" colour TFT active matrix, wide LED

Contrast Ratio : 1300:1 (typ)

Viewing Angles : 178° horizontal, 178° vertical

Brightness : 450 cd/m2 (typ)

Display Area : 36.6" horizontal x 20.6" vertical; 42" diagonal

Optimum Resolution : 1920x1080, 0.485mm dot pitch

Response Time : 12ms

Aspect Ratio : 16:9

Panel Surface : Anti-glare, hard coating (3H)

#### DIMENSIONS

Physical (WxHxD) : 39" x 23" x 1.5"

(991.7mm x 584.3mm x 37.5mm)

#### PACKAGE CONTENTS

LCD display, power cable, remote control with batteries, User Guide CD

#### AUDIO

Amplifier : 10-watt / 8 ohm x2

#### INPUT

Video Input : HDMI, DVI, component, VGA, DP (Display Port)

Video Output : VGA, component, DVI (Loop through)

Control Input/Output : RS-232/RJ45

#### INPUT SIGNAL

TV/Video Comp. : 480i, 480p, 720p, 1080i, 1080p

## CONNECTOR

Digital : HDMI, DVI, DP, RGB, A/V, Component

Power : 3-pin plug

Analog : 9-pin mini D-sub (VGA)

## POWER

Voltage : AC 100–240V (universal), 50–60Hz

Consumption : 115W (typ)

## CONTROLS

Picture : Picture mode, contrast, brightness, colour temperature, temperature adjust, sharpness

Front Panel : Power, Exit, +, –, Menu/Enter

Special : Aspect ratio, over scan, power save, image retention, auto adjustment, monitor ID, reset

Audio : Volume, mute, audio source

Diagnostic : Thermal, back light, ambient, 5V detect, 12 detect

Input : VGA, DVI, HDMI, YPbPr, DP

OSD Setting : Languages, OSD H. position, OSD V. position, OSD timer

VGA Setting : Auto adjustment, clock, phase, sharpness, H. position, V. position

## OPTIONAL ACCESSORIES AVAILABLE

Stand (STND-019), Wall Mount (WMK-013), Wall Mount with Locking Media Player Cradle (WMK-028), Speaker (SPK-012)

## VESA MOUNT COMPLIANT

VESA 400mm x 400mm

## WEIGHT

Gross : 34.8 lb. (15.8 kg)

Net : 27.8 lb. (12.6 kg)

## OPERATING CONDITIONS

Humidity : 10–80% (non-condensing)

Temperature (landscape) : 32–104°F (0–40°C)

Temperature (portrait) : 41–95°F (5–35°C)

## RECYCLE/DISPOSAL

Please dispose of in accordance with local, state, or federal laws.