

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



ViewSonic
See the difference™

Nazwa

**Monitor Viewsonic Slim Commercial LED
Display CDP4737-L**

Cena

0,00 zł

Producent

ViewSonic

OPIS PRODUKTU

SPECIFICATIONS

COLORS

Black

LCD

Type : 47" colour TFT active matrix, wide LED

Contrast Ratio : 1300:1 (typ)

Viewing Angles : 178° horizontal, 178° vertical

Brightness : 450 cd/m2 (typ)

Display Area : 40.9" horizontal x 23" vertical; 47" diagonal

Optimum Resolution : 1920 x 1080, .630mm dot pitch

Response Time : 12ms

Light Source : Long Life, 50,000hrs. (typ)

Aspect Ratio : 16:9

Panel Surface : Anti-glare, hard coating (3H)

Dynamic Contrast Ratio : 50,000:1

DIMENSIONS

Physical (WxHxD) : 43.5" x 25.5" x 1.5" (1105mm x 646.4mm x 37.4mm)

PACKAGE CONTENTS

CDP5537-L display, power cable, remote control with batteries, User Guide CD

AUDIO

Amplifier : 10-watt / 8 ohm x 2

INPUT

Video Input : HDMI, DVI, component, VGA, DP (Display Port)

Video Output : VGA, component, DVI (Loop through)

Control Input/Output : RS-232

INPUT SIGNAL

TV/Video Comp. : 480i, 480p, 720p, 1080i, 1080p

CONNECTOR

Digital : HDMI, DVI, DP, RGB, A/V, Component

Power : 3-pin plug

Analog : 9-pin mini D-sub (VGA)

POWER

Voltage : AC 100–240V (universal), 50–60Hz

Consumption : 140W (typ)

CONTROLS

Picture : Picture mode, contrast, brightness, colour temperature, temperature adjust, sharpness

Front Panel : Power, Exit, +, –, Menu/Enter

Special : Aspect ratio, over scan, power save, image retention, auto adjustment, monitor ID, reset

Audio : Volume, mute, audio source

Diagnostic : Thermal, back light, ambient, 5V detect, 12 detect

Input : VGA, DVI, HDMI, YPbPr, DP

OSD Setting : Languages, OSD H. position, OSD V. position, OSD timer

VGA Setting : Auto adjustment, clock, phase, sharpness, H. position, V. Position

OPTIONAL ACCESSORIES AVAILABLE

Stand.....STND-019

Wall Mount.....WMK-013

VESA MOUNT COMPLIANT

VESA 400mm x 400mm

WEIGHT

Gross : 41.7 lb. (18.9 kg)

Net : 38.6 lb. (17.5 kg)

OPERATING CONDITIONS

Humidity : 10–80% (non-condensing)

Temperature (landscape) : 32–104°F (0–40°C)

Temperature (portrait) : 41–95°F (5–35°C)

RECYCLE/DISPOSAL

Please dispose of in accordance with local, state, or federal laws.