

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



ViewSonic 
See the difference™

Nazwa **Monitor ViewSonic VP3881**

Cena **0,00 zł**

Producent **ViewSonic**

OPIS PRODUKTU

VESA Compatible (Wall Mount 100 x 100 mm)

Menu Controls

USB 3.1 Type A (x3)

USB 3.1 Type B

USB 3.1 Type C

HDMI (x2)

DisplayPort

Audio In

Audio Out

DC In

Kensington Lock Slot

PARAMETRY:

LCD PANEL

Monitor Size : 38"W (37.5" Viewable)

Panel Technology : IPS TFT LCD

Resolution : WQHD+ 3840 x 1600

Display Area : 879.67 mm (H) x 366.53 mm (V)

Aspect Ratio : 21:9

Brightness : 300 cd/m2 (Typ)

Contrast Ratio : 1000:1 (Typ)

Dynamic Contrast Ratio : 20,000,000:1

Viewing Angle : 178 degrees / 178 degrees (Typ)

Refresh Rate : 60Hz

Response Time : GTG: 5 ms (Typ)

Colours : 1.07 Billion colours (10bit)

Colour Gamut : Adobe RGB: 75.67% Coverage / 79.67% Size (Typ)

NTSC:76.12% Coverage / 72.71% Size (Typ)

sRGB:99.52% Coverage / 107.4% Size (Typ)
REC709:99.52% Coverage / 107.4% Size (Typ)
SMPTE-C:100% Coverage / 116.06% Size (Typ)
EBU:98.04% Coverage / 106.19% Size (Typ)
DCI-P3: 79.22% Coverage / 79.22% Size (Typ)
Pixel Size : 0.229 mm (H) x 0.229 mm (V)

INPUT SIGNAL

Frequency : HDMI/ DisplayPort/ Type-C: Fh = 15 ~ 135KHz ; Fv = 24 ~ 75Hz

Sync : HDMI: TMDS

DisplayPort/ Type-C: Mini-Packet

COMPATIBILITY

PC : PC Compatibles (3840 x 1600 HDMI/DisplayPort Non-Interlaced)

Mac® : Power Mac (up to 3840 x1600 HDMI/DisplayPort)

CONNECTOR

Digital : DisplayPort 1.4 HDR ready x 1

HDMI 2.0 x 2

Type-C x 1

Analog : N/A

Audio Out : 3.5mm Mini Phone Jack Audio out x 1

Audio In : 3.5mm Mini Phone Jack Audio in x 1

SPEAKERS

5W * 2

USB

Upstream: USB 3.1 Gen 1 Type-C x 1 and Type-B x1

Downstream: USB 3.1 Gen 1 Type-A x 3

POWER

Power : DC connector x 1

Voltage : AC 100-240V (Universal); 50/60Hz

Consumption : 66W

Optimize : 57W

Conserve : 48W

MODEL COLOUR

Black

ERGONOMICS

Tilt : -1.0° ~ 21.0°

Swivel : 120°

Pivot : N/A

Height Adjustment : 0~130 mm

WALL MOUNT

VESA® : 100 mm x 100 mm

OPERATING CONDITIONS

Temperature (° F / ° C) : 32°F to 104°F (0°C to 40°C)

Humidity : 20% to 90% (no condensation)

DIMENSIONS (W X H X D) (MM)

Physical With Stand (mm) : 896 mm (W) x 629 mm (H) x 299 mm (D)

Physical Without Stand (mm) : 896 mm (W) x 398 mm (H) x 103 mm (D)

Packaging (mm) : 1046 mm (W) x 490 mm (H) x 375 mm (D)

WEIGHT

Net With Stand (kg) : 12.69 kg

Net Without Stand (kg) : 7.97 kg

Gross (kg) : 19.88 kg

REGULATIONS

CB, CE, WEEE, RoHS, ErP, REACH, FCC-B, Energy Star, CU / EAC, UkrSEPRO

PACKAGE CONTENTS

LCD Display

AC/DC Adapter

Power Cable (1.8M)

DisplayPort Cable (1.8M)

HDMI 2.0 Cable (1.8M)

USB3.1 Gen.1 Type C Cable(1.8M)

USB 3.0 UpStream Cable (Type B to A) (1.8M)

Audio Cable (1.8M)

Quick Start Guide

ViewSonic Wizard CD-ROM

*Actual content may differ from market to market