

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



ViewSonic
See the difference™

Nazwa **Projektor VIEWSONIC LS625WP**

Cena **0,00 zł**

Producent **ViewSonic**

OPIS PRODUKTU

Specyfikacja techniczna:

SPECIFICATION

Projection System: 0.65" WXGA

Native Resolution: 1280x800

DMD Type: DC3

Brightness: 3200 ANSI Lumens

Contrast Ratio with SuperEco Mode: 2500000:1

Display Colour: 1.07 Billion Colours

Light Source Type: Laser Phosphor system

Light Source Life (Normal): up to 20000

Light Source Life (SuperEco): up to 20000

Lamp Watt: Nichia MCD

Lens: F=2.8, f=7.51mm

Projection Offset: 115.2%+/-5%

Throw Ratio: 0.52

Image Size: 60"~300"

Throw Distance: 0.78m-1.12m (87" @ 0.97m)

Keystone: H:+/-40° , V:+/-40°

Optical Zoom: Fixed

Digital Zoom: 0.8x ~ 2.0x

Audible Noise (Normal): 34dB (TBD)

Audible Noise (Eco): 30dB (TBD)

Input Lag: 16ms

Resolution Support: VGA(640 x 480) to FullHD(1920 x 1080)

HDTV Compatibility: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p

Video Compatibility: NTSC, PAL, SECAM

Horizontal Frequency: 15K~102KHz

Vertical Scan Rate: 23~120Hz

Interactive Camera: Optional (vTouch-10s)

INPUT

Computer in (share with component): 2

Composite: 1

S-Video: 1

Component (RCAx3): share w/ Computer in

Audio-in (3.5mm): 1

HDMI: 2 (Back)

(HDMI 1.4/ HDCP 1.4) x2

OUTPUT

Monitor out: 1

Audio out (3.5mm): 1

Speaker: 10W x 2

USB Type A (Power): 1 (5V/ 1.5A)

12V Trigger (3.5mm): 1 (3.5mm)

CONTROL

RS232 (DB 9-pin male): 1

RJ45: 1

USB Type Mini B (Services): 1

OTHERS

Power Supply Voltage: 100-240V+/- 10%, 50/60Hz AC

Power Consumption: Normal: 305W

Standby: <0.5W

Operating Temperature: 0~40°C

Net Weight: 6.2kg

Dimensions (WxDxH) with Adjustment Foot: 383x291x147mm

OSD Language: English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese

STANDARD ACCESSORY

Power Cord: 1

VGA Cable: 1

Remote Control: 1 (w/Laser pointer)

QSG: 1

Lens Cover: Yes