

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



ViewSonic
See the difference™

Nazwa **Projektor VIEWSONIC LS700HDE**

Cena **0,00 zł**

Producent **ViewSonic**

OPIS PRODUKTU

Specyfikacja techniczna

SPECIFICATION

Projection System: 0.47" 1080p

Native Resolution: 1920x1080

DMD Type: DC3

Brightness: 4000 ANSI Lumens

Contrast Ratio with SuperEco Mode: 3000000:1

Display Colour: 1.07 Billion Colours

Light Source Type: Laser Phosphor system

Light Source Life (Normal): up to 20000

Light Source Life (SuperEco): up to 20000

Lamp Watt: Nichia MCD

Lens: F=1.9-2.49, f=12-15.6mm

Projection Offset: 100%+/-5%

Throw Ratio: 1.13~1.47

Image Size: 60" - 300"

Throw Distance: 1.5-8.79m(100"@2.5m)

Keystone: H:+/-40°, V:+/-40°

Optical Zoom: 1.3X

Digital Zoom: 0.8x ~ 2.0x

Audible Noise (Normal): 34dB

Audible Noise (Eco): 32dB

Input Lag: 16ms (TBD)
Resolution Support: VGA(640 x 480) to FullHD(1920 x 1080)
HDTV Compatibility: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility: NTSC, PAL, SECAM
Horizontal Frequency: 15K~102KHz
Vertical Scan Rate: 23~120Hz

INPUT

Computer in (share with component): 2
Composite: 1
Audio-in (3.5mm): 1
HDMI: 2
(HDMI 1.4a/HDCP1.4 x2)

OUTPUT

Monitor out: 1
Audio out (3.5mm): 1
Speaker: 2W
USB Type A (Power): 1 (5V/ 1.5A)

CONTROL

RS232 (DB 9-pin male): 1
RJ45: 1
USB Type Mini B (Services): 1

OTHERS

Power Supply Voltage: 100-240V+/- 10%, 50/60Hz AC
Power Consumption: Normal: 260W
Standby: <0.5W
Operating Temperature: 0~40°C
Net Weight: 7.14Kg

Dimensions (WxDxH) with Adjustment Foot: 396x314x157mm

OSD Language: English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese

STANDARD ACCESSORY

Power Cord: 1
VGA Cable: 1
Remote Control: 1
QSG: 1

CECHY PRODUKTU

Model/Seria	LS700HDE
Technologia	DLP
Rozdzielczość (Podstawowa)	FULL HD
Format Obrazu	16:9
Jasność	4000
Kontrast (...:1)	3000000
Żródło Światła	LASER
Żywotność Żródła Światła (Ilość Godzin)	20000
Wsp. Powiększenia/Rzutu (Throw Ratio) Minimalny (...:1)	1.13

Wsp. Powiększenia/Rzutu (Throw Ratio) Maksymalny (...:1) **1.47**