

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



**ViewSonic**   
See the difference™

Nazwa **Projektor VIEWSONIC PG706WU**

Cena **0,00 zł**

Producent **ViewSonic**

## OPIS PRODUKTU

Specyfikacja techniczna

### SPECIFICATION

Projection System: 0.48" WUXGA

Native Resolution: 1920x1200

DMD Type: DC3

Brightness: 4000 ANSI Lumens

Contrast Ratio with SuperEco Mode: 12000:1

Display Colour: 1.07 Billion Colours

Light Source Type: Lamp

Light Source Life (Normal): 4000

Light Source Life (SuperEco): 20000

Lamp Watt: 245W

Lens: F=2.0~2.05, f=15.843-17.445mm

Projection Offset: 100%+/-6%

Throw Ratio: 1.5-1.65

Optical Zoom: 1.1x

Digital Zoom: 0.8x-2.0x

Image Size: 30"-300"

Throw Distance: 0.97m-10.66m

(100"@3.23m)

Keystone: +/- 40° (V)

Audible Noise (Normal): 32dB

Audible Noise (Eco): 27dB

Input Lag: 16ms

Resolution Support: VGA(640 x 480) to WUXGA\_RB(1920 x 1200)

\*RB-Reduced Blanking

HDTV Compatibility: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p

Video Compatibility: NTSC, PAL, SECAM

Horizontal Frequency: 15K-102KHz

Vertical Scan Rate: 23-120Hz

#### INPUT

Computer in (share with component): 1

Composite: 1

S-Video: 1

HDMI: 2

(HDMI 1.4/ HDCP 1.4)

Audio-in (3.5mm): 1

RJ45 Input: 1

(LAN control)

#### OUTPUT

Monitor out: 1

Audio out (3.5mm): 1

Speaker: 10W

USB Type A (Power): 1 (5V/ 1.5A)

#### CONTROL

RS232 (DB 9-pin male): 1

RJ45: 1

#### OTHERS

Power Supply Voltage: 100-240V+/- 10%, 50/60Hz

(AC in)

Power Consumption: Normal: 355W

Standby: <0.5W

Operating Temperature: 0~40°C

Net Weight: 2.79kg

Dimensions (WxDxH) with Adjustment Foot: 312x222x108mm

OSD Language: English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish,

Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic,

Vietnamese, Greek Total 23 languages

#### STANDARD ACCESSORY

Power Cord: 1

VGA Cable: 1

Remote Control: 1

(w/ laser pointer)

QSG: 1

#### OPTIONAL ACCESSORY

Lamp/Light Source: RLC-120