

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



ViewSonic
See the difference™

Nazwa **Projektor ViewSonic PJD6221**

Cena **0,00 zł**

Producent **ViewSonic**

OPIS PRODUKTU

SPECIFICATIONS

COLORS

Black

COMPATIBILITY

PC : VGA to SXGA

Mac® : Up to 1024×768 (may require Mac Adapter)

DIMENSIONS

Physical (WxHxD) : 280 × 108 × 218 (mm) / 11 × 4.25 × 8.58 (inch)

PACKAGE CONTENTS

ViewSonic projector, power cable, VGA cable, remote control with batteries, lens cap, Quick Start Guide, ViewSonic Wizard CD (with User Guide)

WARRANTY

3-year limited warranty on parts, 1-year limited warranty on lamp

AUDIO

Speaker : 2W

INPUT SIGNAL

Frequency : Fh: 31-100 KHz, Fv: 50-120 Hz

Computer And Video : NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SD 480i and 576i (24fps, 25fps and 30fps), ED 480p and 576p (24fps, 25fps and 30fps),

HD 720p, 1080i (24fps, 25pfs and 30fps)

CONNECTOR

Audio Out : 1 × 3.5mm mini jack

PC RGB Input : 2 × 15-pin mini D-sub
S-Video Input : 1 × 4-pin mini-DIN
PC RGB Output : 1 × 15-pin mini D-sub
Audio Input : 1 × 3.5mm mini jack
Control : 1×RS-232 (9 Pin D-sub) / RJ45
Composite Input : 1 × RCA jack

POWER

Voltage : 90~240VAC (Auto Switching), 50/60Hz (universal)
Consumption : 235W (Typical) / <1W (Stand-by mode)

CONTROLS

Basic : POWER, Keystone/Arrow keys, Left/BLANK, MENU/EXIT, Right/Panel key

OSD : lock, AUTO, MODE/ENTER, SOURCE

Picture: Brightness, Contrast, Color Setting, Keystone, Aspect Ratio, Image, White Intensity, Gamma, 3D Sync, 3D Sync Invert.

Computer Image: Frequency, Tracking, H Position, V Position

Video Image: Saturation, Sharpnes, Tint

Setting: Manu Position, Projection, Signal Type, Lamp Hour, Lamp Hour

Reset, Filter Mode, Filter Hours, Filter Hours Reset, Power Saving, Auto

Source, ECO Mode, High Altitude, OSD Timeout

Advance: Blank Screen, Password Word, Screen Capture, Start up Screen,

Text Shot, Digital Zoom, DCR, Close Captions, Brilliant Color.

OPERATING CONDITIONS

Temperature : 0°C-40°C (32°F-104°F)

Humidity : 10% - 90% (non-condensing)

Altitude : 0~1,800m (6000ft), operational up to 3,048m (10000ft)

WEIGHT

Net : 2.7 kg (5.95 lb)

DISPLAY

Contrast Ratio □ : 3000:1 (with DCR)

Display Size : 0.8m - 7.6m (30" - 300")

Aspect Ratio : 4:3 (native) & 16:9

Throw Distance : 1.2m-10m

Throw Ratio : 1.6:1-1.9:1

Brightness : 2900 Lumens

Color Wheel : 6-Seg RGBCYW / 7200rpm

Color Gamut : 85 % NTSC 1931 CIE

Lamp Life (Normal / Eco / Dynamic Eco) : 4000 / 5000 (hours)

Type : 1.4 cm / 0.55" Digital Micromirror Device (DLP™)

Resolution : XGA 1024x768 (Native) / SXGA 1280×1024 (compressed)

Keystone : Vertical digital keystone correction: +/- 40 degrees

Lamp : 180watt (RLC-050)

Lens : 1.2× Manual optical zoom / Manual optical focus

Color Depth : 24 bits, 16.7M Colors (8+8+8)

NOISE LEVEL

Normal : 31dB

Eco-mode : 29dB

LANGUAGE

English/ Dutch/French / Spanish/Italian/ Korean/Thai/Portuguese/ T.

Chines/ S. Chinese /Japanese /Russian /German /Swedish /Turkish /

Finnish /Polish