

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Lens Not Included

Nazwa **Projektor Viewsonic Pro10100 (bez obiektywu)**

Cena **11 669,00 zł**

Producent **ViewSonic**

OPIS PRODUKTU

DISPLAY

Type

TI DMD 0.7" XGA 2xLVDS Type A DMD, Dark chip 3

Resolution

XGA 1024x768 (native)

Lens

(Sold Separately)LEN-008: 1.28x

LEN-009: 1.25x

LEN-010: 1.9x

Keystone

Vertical digital keystone correction (+/- 20°)

Display Size

50 – 300 in. (1.27 – 7.6m)

Throw Distance

LEN-008: 3.3 – 25.2 ft. (1.01 – 7.68m)

LEN-009: 4.2 – 31.6 ft. (1.28 – 9.63m)

LEN-010: 5.3 – 60.0 ft. (1.61 – 18.29m)

Throw Ratio

LEN-008: 0.99 – 1.26:1

LEN-009: 1.26 – 1.58:1

LEN-010: 1.58 – 3.00:1

Lamp Type

370 watt

Lamp Life (normal/eco-mode)

1500 / 2000 hours*

Brightness

6000 Lumens

Contrast Ratio

4,400:1 (DCR)

Aspect Ratio

4:3 (native)

Color Depth

30 bits, 1.07B Color (10+10+10)

INPUT SIGNAL

Computer and Video

NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SECAM (B, D, G, K, K1, L), SD 480i and 576i, ED 480p and 576p, HD 720p, 1080i, 1080p

Frequency

Fh: 15–100KHz, Fv: 24–87Hz

COMPATIBILITY

PC

VGA to WSXGA+ (1680x1050)

Mac®

Up to 1152x870 (may require MAC adaptor)

CONNECTOR

Audio Input

3.5mm mini jack

Audio Out

3.5mm mini jack

RGB Input

15-pin mini D-sub

Composite Input

RCA jack

S-Video Input

4-pin mini-DIN

Component

BNC (RGBHV, Y/Pb/Pr, Y/Cb/Cr)

RGB Output

15-pin mini D-sub

Control

RS-232 (DB-9)

Digital

HDMI

Screen Trigger

4mm DC Jack

AUDIO

Speakers

10-watt (x1)

POWER

Voltage

100~240VAC (Auto Switching), 50/60Hz (universal)

Consumption

480w (typ.) / <0.5w (standby mode)

CONTROLS

Basic

Power, arrow keys, menu, exit, sync, enter, source, shift, focus, zoom, info

OSD

Picture, Screen, Setting, Options (See user guide for full OSD functionality)

OPERATING CONDITIONS

Temperature

41°F–104°F (5°C–40°C)

Humidity

0%–85% (non-condensing)

Altitude

0–6,000 ft (1,800m), operational up to 10,000 ft (3048m)

NOISE LEVEL

Normal

38dB

Eco-Mode

33dB

DIMENSIONS (WxHxD)

Physical

17.8 x 8.3 x 15.4 in. / 453 x 212 x 390 mm

Packaging

23.2 x 16.1 x 19.7 in. / 590 x 408 x 500 mm

WEIGHT

Net

30.6 lb. / 13.9 kg

Gross

38.1 lb. / 17.3 kg

Regulations

CB, UL/cUL, FCC (including ICES-004), CE, TUV-GS, C-Tick, CCC, WEEE, RoHS, ErP, REACH, SVHC

PACKAGE CONTENTS

Pro10100 projector (without lens), power cable, VGA cable, remote control with batteries, Quick Start Guide, ViewSonic Wizard CD (with User Guide)

Warranty

3-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service**